

---

**lib3mf**

***Release v2.2.0***

**3MF Consortium**

**Aug 24, 2021**



# CONTENTS

<b>1</b>	<b>API documentation</b>	<b>3</b>
1.1	C++-language bindings . . . . .	3
1.1.1	Minimal Example Project . . . . .	4
1.1.2	General Information . . . . .	6
1.1.3	API-Classes . . . . .	16
1.2	C-language bindings . . . . .	52
1.3	Python-language bindings . . . . .	52
1.4	Pascal-language bindings . . . . .	52
1.5	C#-language bindings . . . . .	52
1.6	Golang-language bindings . . . . .	52
1.7	NodeJS-language bindings . . . . .	53
<b>2</b>	<b>Obtaining lib3mf</b>	<b>55</b>
<b>3</b>	<b>Using lib3mf</b>	<b>57</b>
<b>4</b>	<b>Meta Information</b>	<b>59</b>
<b>5</b>	<b>Indices and tables</b>	<b>61</b>
	<b>Index</b>	<b>63</b>



Welcome! This is the documentation for lib3mf v2.2.0.

lib3mf is an implementation of the 3D Manufacturing Format file standard.

It provides 3MF reading and writing capabilities, as well as conversion and validation tools for input and output data. lib3mf runs on Windows, Linux and MacOS and offers a clean and easy-to-use API in various programming languages to speed up the development and keep integration costs at a minimum.

As 3MF shall become an universal 3D Printing standard, its quick adoption is very important. This library shall lower all barriers of adoption to any possible user, let it be software providers, hardware providers, service providers or middleware tools.



## API DOCUMENTATION

- C++
- C
- Python
- Pascal
- C#
- Golang
- NodeJS

## 1.1 C++-language bindings

This space describes the usage of lib3mf in a C++ host application.

The C++-language bindings come in two different flavors:

Cpp

CppDynamic

If you include the header `Cpp/lib3mf_implicit.hpp`, lib3mf will be loaded dynamically during *load-time* of your host application through your operating system's mechanism for loading libraries.

```
Lib3MF::PWrapper wrapper = CWrapper::loadLibrary();
```

The shared library file `lib3mf.*` needs to reside in a path that your operating systems checks when loading libraries.

If you include the header `CppDynamic/lib3mf_dynamic.hpp`, Lib3MF will be loaded dynamically during *run-time* of your host application through an explicit call to

Linux

Mac OSX

Windows

```
Lib3MF::PWrapper wrapper = Lib3MF::CWrapper::loadLibrary("LibraryLocation/lib3mf.so");
```

```
Lib3MF::PWrapper wrapper = Lib3MF::CWrapper::loadLibrary("LibraryLocation/lib3mf.dylib");
```

```
Lib3MF::PWrapper wrapper = Lib3MF::CWrapper::loadLibrary("LibraryLocation/lib3mf.dll");
```

i.e. you need to explicitly provide the location of the shared library file `lib3mf.*`.

The `Lib3MF::PWrapper` object provides access to all functionality within `lib3mf`.

Both flavors of the C++-bindings are header-only which makes it extremely easy to include them into existing projects:

### 1.1.1 Minimal Example Project

Minimal application code:

Cpp

CppDynamic

```
#include <iostream>
#include "lib3mf_implicit.hpp"

int main()
{
    try
    {
        auto wrapper = Lib3MF::CWrapper::loadLibrary();
        Lib3MF_uint32 nMajor, nMinor, nMicro;
        wrapper->GetLibraryVersion(nMajor, nMinor, nMicro);
        std::cout << "Lib3MF.Version = " << nMajor << "." << nMinor << "." << nMicro;
        std::string sPreReleaseInfo;
        if (wrapper->GetPrereleaseInformation(sPreReleaseInfo)) {
            std::cout << "-" << sPreReleaseInfo;
        }
        std::string sBuildInfo;
        if (wrapper->GetBuildInformation(sBuildInfo)) {
            std::cout << "+" << sBuildInfo;
        }
        std::cout << std::endl;
    }
    catch (std::exception &e)
    {
        std::cout << e.what() << std::endl;
        return 1;
    }
    return 0;
}
```

```
#include <iostream>
#include "lib3mf_dynamic.hpp"

int main()
{
    try
    {
        std::string libpath = (""); // TODO: put the location of the Lib3MF-library file
        ↪ here.
    }
}
```

(continues on next page)



(continued from previous page)

```

    auto wrapper = Lib3MF::CWrapper::loadLibrary(libpath + "/lib3mf."); // TODO: add_
    ↪correct suffix of the library
    Lib3MF_uint32 nMajor, nMinor, nMicro;
    wrapper->GetLibraryVersion(nMajor, nMinor, nMicro);
    std::cout << "Lib3MF.Version = " << nMajor << "." << nMinor << "." << nMicro;
    std::string sPreReleaseInfo;
    if (wrapper->GetPrereleaseInformation(sPreReleaseInfo)) {
        std::cout << "-" << sPreReleaseInfo;
    }
    std::string sBuildInfo;
    if (wrapper->GetBuildInformation(sBuildInfo)) {
        std::cout << "+" << sBuildInfo;
    }
    std::cout << std::endl;
}
catch (std::exception &e)
{
    std::cout << e.what() << std::endl;
    return 1;
}
return 0;
}

```

CMakeLists.txt for minimal project:

Cpp

CppDynamic

```

cmake_minimum_required(VERSION 3.5)

set(CMAKE_CURRENT_BINDING_DIR ${CMAKE_CURRENT_SOURCE_DIR}/.)
project(Lib3MFExample_CPPImplicit)
set(CMAKE_CXX_STANDARD 11)
add_executable(Lib3MFExample_CPPImplicit "${CMAKE_CURRENT_SOURCE_DIR}/Lib3MF_example.cpp"
    ↪")
find_library(LIB3MFLOCATION lib3mf "${CMAKE_CURRENT_SOURCE_DIR}/../Implementations/*/"
    ↪"/")
target_link_libraries(Lib3MFExample_CPPImplicit ${LIB3MFLOCATION})
target_include_directories(Lib3MFExample_CPPImplicit PRIVATE "${CMAKE_CURRENT_BINDING_
    ↪DIR}")

```

```

cmake_minimum_required(VERSION 3.5)

set(CMAKE_CURRENT_BINDING_DIR ${CMAKE_CURRENT_SOURCE_DIR}/.)
project(Lib3MFExample_CPPDynamic)
set(CMAKE_CXX_STANDARD 11)
add_executable(Lib3MFExample_CPPDynamic "${CMAKE_CURRENT_SOURCE_DIR}/Lib3MF_example.cpp")
if (UNIX)
    target_link_libraries(Lib3MFExample_CPPDynamic ${CMAKE_DL_LIBS})
endif (UNIX)
target_include_directories(Lib3MFExample_CPPDynamic PRIVATE "${CMAKE_CURRENT_BINDING_DIR"
    ↪")

```

The examples in the Cpp/CppDynamic-folders of the binary SDK follow exactly this pattern.

The remainder of this space is an in-depth API-reference for the functionality of lib3mf.

## 1.1.2 General Information

### The wrapper class CWrapper

class Lib3MF::CWrapper

All types of the 3MF Library reside in the namespace Lib3MF and all functionality of the 3MF Library resides in Lib3MF::CWrapper.

A suitable way to use Lib3MF::CWrapper is as a singleton.

void **GetLibraryVersion**(*Lib3MF\_uint32* &nMajor, *Lib3MF\_uint32* &nMinor, *Lib3MF\_uint32* &nMicro)  
retrieves the binary version of this library.

#### Parameters

- **nMajor** – returns the major version of this library
- **nMinor** – returns the minor version of this library
- **nMicro** – returns the micro version of this library

bool **GetPrereleaseInformation**(std::string &sPrereleaseInfo)  
retrieves prerelease information of this library.

**Returns** Does the library provide prerelease version?

**Parameters** **sPrereleaseInfo** – retrieves prerelease information of this library.

bool **GetBuildInformation**(std::string &sBuildInformation)  
retrieves build information of this library.

**Returns** Does the library provide build version?

**Parameters** **sBuildInformation** – retrieves build information of this library.

void **GetSpecificationVersion**(const std::string &sSpecificationURL, bool &bIsSupported,  
*Lib3MF\_uint32* &nMajor, *Lib3MF\_uint32* &nMinor, *Lib3MF\_uint32*  
&nMicro)

retrieves whether a specification is supported, and if so, which version.

#### Parameters

- **sSpecificationURL** – URL of extension to check
- **bIsSupported** – returns whether this specification is supported
- **nMajor** – returns the major version of the extension (if IsSupported)
- **nMinor** – returns the minor version of the extension (if IsSupported)
- **nMicro** – returns the micro version of the extension (if IsSupported)

*PModel* **CreateModel**()

creates an empty model instance.

**Returns** returns an empty model instance

void **Release**(*CBase* \*pInstance)  
releases shared ownership of an object instance

**Parameters** **pInstance** – the object instance to release

void **Acquire**(*CBase* \*pInstance)  
acquires shared ownership of an object instance

**Parameters** **pInstance** – the object instance to acquire

void **SetJournal**(const std::string &sJournalPath)  
Sets the journal file path

**Parameters** **sJournalPath** – File name of the journal file

bool **GetLastError**(*CBase* \*pInstance, std::string &sLastErrorMessage)  
Retrieves the last error string of an instance

**Parameters**

- **pInstance** – Object where the error occurred.
- **sLastErrorMessage** – Last Error String

**Returns** Returns if the instance has a last error.

void **RetrieveProgressMessage**(const eProgressIdentifier eTheProgressIdentifier, std::string &sProgressMessage)

Return an English text for a progress identifier.[Note: this is the only function you can call from your callback function.

**Parameters**

- **eTheProgressIdentifier** – the progress identifier that is passed to the callback function
- **sProgressMessage** – English text for the progress identifier

*sColor* **RGBAToColor**(const *Lib3MF\_uint8* nRed, const *Lib3MF\_uint8* nGreen, const *Lib3MF\_uint8* nBlue, const *Lib3MF\_uint8* nAlpha)

Creates a Color from uint8 RGBA values

**Parameters**

- **nRed** – Red value of color (0-255)
- **nGreen** – Green value of color (0-255)
- **nBlue** – Blue value of color (0-255)
- **nAlpha** – Alpha value of color (0-255)

**Returns** Assembled color

*sColor* **FloatRGBAToColor**(const *Lib3MF\_single* fRed, const *Lib3MF\_single* fGreen, const *Lib3MF\_single* fBlue, const *Lib3MF\_single* fAlpha)

Creates a Color from uint8 RGBA values

**Parameters**

- **fRed** – Red value of color (0-1)
- **fGreen** – Green value of color (0-1)
- **fBlue** – Blue value of color (0-1)
- **fAlpha** – Alpha value of color (0-1)

**Returns** Assembled color

void **ColorToRGBA**(const *sColor* &TheColor, *Lib3MF\_uint8* &nRed, *Lib3MF\_uint8* &nGreen, *Lib3MF\_uint8* &nBlue, *Lib3MF\_uint8* &nAlpha)

Calculates uint8-RGBA-values from a Color

**Parameters**

- **TheColor** – Color to handle
- **nRed** – Red value of color (0-255)
- **nGreen** – Green value of color (0-255)
- **nBlue** – Blue value of color (0-255)
- **nAlpha** – Alpha value of color (0-255)

void **ColorToFloatRGBA**(const *sColor* &TheColor, *Lib3MF\_single* &fRed, *Lib3MF\_single* &fGreen, *Lib3MF\_single* &fBlue, *Lib3MF\_single* &fAlpha)

Calculates float-RGBA-values from a Color

**Parameters**

- **TheColor** – Color to handle
- **fRed** – Red value of color (0-1)
- **fGreen** – Green value of color (0-1)
- **fBlue** – Blue value of color (0-1)
- **fAlpha** – Alpha value of color (0-1)

*sTransform* **GetIdentityTransform**()

Creates an identity transform

**Returns** Transformation matrix.

*sTransform* **GetUniformScaleTransform**(const *Lib3MF\_single* fFactor)

Creates a uniform scale transform

**Parameters** **fFactor** – Factor in X, Y and Z

**Returns** Transformation matrix.

*sTransform* **GetScaleTransform**(const *Lib3MF\_single* fFactorX, const *Lib3MF\_single* fFactorY, const *Lib3MF\_single* fFactorZ)

Creates a scale transform

**Parameters**

- **fFactorX** – Factor in X
- **fFactorY** – Factor in Y
- **fFactorZ** – Factor in Z

**Returns** Transformation matrix.

*sTransform* **GetTranslationTransform**(const *Lib3MF\_single* fVectorX, const *Lib3MF\_single* fVectorY, const *Lib3MF\_single* fVectorZ)

Creates an translation transform

**Parameters**

- **fVectorX** – Translation in X
- **fVectorY** – Translation in Y
- **fVectorZ** – Translation in Z

**Returns** Transformation matrix.

typedef std::shared\_ptr<*CWrapper*> Lib3MF::P**Wrapper**

## Types used in the 3MF Library

### Simple types

```
typedef uint8_t Lib3MF_uint8
typedef uint16_t Lib3MF_uint16
typedef uint32_t Lib3MF_uint32
typedef uint64_t Lib3MF_uint64
typedef int8_t Lib3MF_int8
typedef int16_t Lib3MF_int16
typedef int32_t Lib3MF_int32
typedef int64_t Lib3MF_int64
typedef float Lib3MF_single
typedef double Lib3MF_double
using Lib3MF_pvoid = void*
using Lib3MFResult = Lib3MF_int32
```

### Enumerations

```
enum class ePropertyType : Lib3MF_int32

    enumerator NoPropertyType = 0
    enumerator BaseMaterial = 1
    enumerator TexCoord = 2
    enumerator Colors = 3
    enumerator Composite = 4
    enumerator Multi = 5

enum class eSlicesMeshResolution : Lib3MF_int32

    enumerator Fullres = 0
    enumerator Lowres = 1

enum class eModelUnit : Lib3MF_int32

    enumerator MicroMeter = 0
    enumerator MilliMeter = 1
    enumerator CentiMeter = 2
    enumerator Inch = 3
    enumerator Foot = 4
    enumerator Meter = 5
```

```
enum class eObjectType : Lib3MF_int32

    enumerator Other = 0
    enumerator Model = 1
    enumerator Support = 2
    enumerator SolidSupport = 3
enum class eTextureType : Lib3MF_int32

    enumerator Unknown = 0
    enumerator PNG = 1
    enumerator JPEG = 2
enum class eTextureTileStyle : Lib3MF_int32

    enumerator Wrap = 0
    enumerator Mirror = 1
    enumerator Clamp = 2
    enumerator NoTileStyle = 3
enum class eTextureFilter : Lib3MF_int32

    enumerator Auto = 0
    enumerator Linear = 1
    enumerator Nearest = 2
enum class eBeamLatticeCapMode : Lib3MF_int32

    enumerator Sphere = 0
    enumerator HemiSphere = 1
    enumerator Butt = 2
enum class eBeamLatticeClipMode : Lib3MF_int32

    enumerator NoClipMode = 0
    enumerator Inside = 1
    enumerator Outside = 2
enum class eBeamLatticeBallMode : Lib3MF_int32

    enumerator None = 0
    enumerator Mixed = 1
    enumerator All = 2
enum class eProgressIdentifier : Lib3MF_int32
```

```

enumerator QUERYCANCELED = 0
enumerator DONE = 1
enumerator CLEANUP = 2
enumerator READSTREAM = 3
enumerator EXTRACTOPCPACKAGE = 4
enumerator READNONROOTMODELS = 5
enumerator READROOTMODEL = 6
enumerator READRESOURCES = 7
enumerator READMESH = 8
enumerator READSLICES = 9
enumerator READBUILD = 10
enumerator READCUSTOMATTACHMENT = 11
enumerator READTEXTURETACHMENTS = 12
enumerator CREATEOPCPACKAGE = 13
enumerator WRITEMODELSTOSTREAM = 14
enumerator WRITEROOTMODEL = 15
enumerator WRITENONROOTMODELS = 16
enumerator WRITEATTACHMENTS = 17
enumerator WRITECONTENTTYPES = 18
enumerator WRITENOBJECTS = 19
enumerator WRITENODES = 20
enumerator WRITETRIANGLES = 21
enumerator WRITESLICES = 22
enumerator WRITEKEYSTORE = 23
enum class eBlendMethod : Lib3MF_int32

    enumerator NoBlendMethod = 0
    enumerator Mix = 1
    enumerator Multiply = 2
enum class eEncryptionAlgorithm : Lib3MF_int32

    enumerator AES256_GCM = 1
enum class eWrappingAlgorithm : Lib3MF_int32

    enumerator RSA_OAEP = 0
enum class eMgfAlgorithm : Lib3MF_int32

```

```
enumerator MGF1_SHA1 = 160
enumerator MGF1_SHA224 = 224
enumerator MGF1_SHA256 = 256
enumerator MGF1_SHA384 = 384
enumerator MGF1_SHA512 = 512
enum class eDigestMethod : Lib3MF_int32

    enumerator SHA1 = 160
    enumerator SHA256 = 256
enum class eCompression : Lib3MF_int32

    enumerator NoCompression = 0
    enumerator Deflate = 1
```

## Structs

All structs are defined as *packed*, i.e. with the

```
#pragma pack (1)
```

```
struct sTriangle
```

```
    Lib3MF_uint32 m_Indices[3]
```

```
struct sTriangleProperties
```

```
    Lib3MF_uint32 m_ResourceID
```

```
    Lib3MF_uint32 m_PropertyIDs[3]
```

```
struct sPosition
```

```
    Lib3MF_single m_Coordinates[3]
```

```
struct sPosition2D
```

```
    Lib3MF_single m_Coordinates[2]
```

```
struct sCompositeConstituent
```

```
    Lib3MF_uint32 m_PropertyID
```

```
    Lib3MF_double m_MixingRatio
```

```
struct sMultiPropertyLayer
```

```
    Lib3MF_uint32 m_ResourceID
```

```
    eBlendMethod m_TheBlendMethod
```



struct **sTex2Coord**

*Lib3MF\_double* **m\_U**

*Lib3MF\_double* **m\_V**

struct **sTransform**

*Lib3MF\_single* **m\_Fields**[4][3]

struct **sBox**

*Lib3MF\_single* **m\_MinCoordinate**[3]

*Lib3MF\_single* **m\_MaxCoordinate**[3]

struct **sColor**

*Lib3MF\_uint8* **m\_Red**

*Lib3MF\_uint8* **m\_Green**

*Lib3MF\_uint8* **m\_Blue**

*Lib3MF\_uint8* **m\_Alpha**

struct **sBeam**

*Lib3MF\_uint32* **m\_Indices**[2]

*Lib3MF\_double* **m\_Radii**[2]

*eBeamLatticeCapMode* **m\_CapModes**[2]

struct **sBall**

*Lib3MF\_uint32* **m\_Index**

*Lib3MF\_double* **m\_Radius**

## Function types

using **ProgressCallback** = void (\*)(bool\*, *Lib3MF\_double*, Lib3MF::eProgressIdentifier, *Lib3MF\_pvoid*)

A callback function

**Returns** Returns whether the calculation should be aborted

**Parameters**

- **dProgressValue** – The value of the progress function: values in the interval [0,1] are progress; < mean no progress update
- **eProgressIdentifier** – An identifier of progress
- **pUserData** – Userdata that is passed to the callback function

using **WriteCallback** = void (\*)(*Lib3MF\_uint64*, *Lib3MF\_uint64*, *Lib3MF\_pvoid*)

Callback to call for writing a data chunk

**Parameters**

- **nByteData** – Pointer to the data to be written
- **nNumBytes** – Number of bytes to write
- **pUserData** – Userdata that is passed to the callback function

using **ReadCallback** = void (\*)(*Lib3MF\_uint64*, *Lib3MF\_uint64*, *Lib3MF\_pvoid*)  
Callback to call for reading a data chunk

**Parameters**

- **nByteData** – Pointer to a buffer to read data into
- **nNumBytes** – Number of bytes to read
- **pUserData** – Userdata that is passed to the callback function

using **SeekCallback** = void (\*)(*Lib3MF\_uint64*, *Lib3MF\_pvoid*)  
Callback to call for seeking in the stream

**Parameters**

- **nPosition** – Position in the stream to move to
- **pUserData** – Userdata that is passed to the callback function

using **RandomNumberCallback** = void (\*)(*Lib3MF\_uint64*, *Lib3MF\_uint64*, *Lib3MF\_pvoid*, *Lib3MF\_uint64\**)  
Callback to generate random numbers

**Parameters**

- **nByteData** – Pointer to a buffer to read data into
- **nNumBytes** – Size of available bytes in the buffer
- **pUserData** – Userdata that is passed to the callback function

**Returns** Number of bytes generated when succeed. 0 or less if failed.

using **KeyWrappingCallback** = void (\*)(*Lib3MF\_AccessRight*, *Lib3MF\_uint8\**, *Lib3MF\_uint8\*\**, *Lib3MF\_pvoid*, *Lib3MF\_uint64\**)  
A callback used to wrap (encrypt) the content key available in keystore resource group

**Parameters**

- **pKEKParams** – The information about the parameters used used to wrap the key to the contents
- **nInBufferBufferSize** – Buffer to the input value. When encrypting, this should be the plain key. When decrypting, this should be the key cipher.
- **nInBufferBufferSize** – buffer of Buffer to the input value. When encrypting, this should be the plain key. When decrypting, this should be the key cipher.
- **nOutBufferBufferSize** – Number of elements in buffer
- **pOutBufferNeededCount** – will be filled with the count of the written elements, or needed buffer size.
- **pOutBufferBuffer** – buffer of Buffer where the data will be placed. When encrypting, this will be the key cipher. When decrypting, this will be the plain key. When buffer is null, neededBytes contains the required bytes to run.
- **pUserData** – Userdata that is passed to the callback function

**Returns** The needed/encrypted/decrypted bytes when succeed or zero when error.

using **ContentEncryptionCallback** = void (\*)(Lib3MF\_ContentEncryptionParams, *Lib3MF\_uint8\**, *Lib3MF\_uint8\*\**, *Lib3MF\_pvoid*, *Lib3MF\_uint64\**)

A callback to encrypt/decrypt content called on each resource encrypted. This might be called several times depending on content size. If Input is not available(either null or size is 0), clients must return the result of authenticated tag generation/validation.

#### Parameters

- **pCEKParams** – The params of the encryption process. Client must set/check AuthenticationTag when closing the encryption/decryption process.
- **nInputBufferSize** – Buffer to the original data. In encrypting, this will be the plain data. If decrypting, this will be the cipher data
- **nInputBufferSize** – buffer of Buffer to the original data. In encrypting, this will be the plain data. If decrypting, this will be the cipher data
- **nOutputBufferSize** – Number of elements in buffer
- **pOutputNeededCount** – will be filled with the count of the written elements, or needed buffer size.
- **pOutputBuffer** – buffer of Buffer to hold the transformed data. When encrypting, this will be the cipher data. When decrypting, this shall be the plain data. If buffer is null, neededBytes return the necessary amount of bytes.
- **pUserData** – Userdata that is passed to the callback function

**Returns** The needed/encrypted/decrypted/verified bytes when succeed or zero when error.

### ELib3MFException: The standard exception class of the 3MF Library

Errors in the 3MF Library are reported as Exceptions. It is recommended to not throw these exceptions in your client code.

class Lib3MF::ELib3MFException

void ELib3MFException::what() const noexcept

Returns error message

**Returns** the error message of this exception

*Lib3MFResult* ELib3MFException::getErrorCode() const noexcept

Returns error code

**Returns** the error code of this exception

### CInputVector: Adapter for passing arrays as input for functions

Several functions of the 3MF Library expect arrays of integral types or structs as input parameters. To not restrict the interface to, say, `std::vector<type>`, and to have a more abstract interface than a location in memory and the number of elements to input to a function the 3MF Library provides a templated adapter class to pass arrays as input for functions.

Usually, instances of CInputVector are generated anonymously (or even implicitly) in the call to a function that expects an input array.

template<typename T>

class Lib3MF::CInputVector

**CInputVector**(const std::vector<*T*> &vec)

Constructs of a CInputVector from a std::vector<*T*>

**CInputVector**(const *T* \*in\_data, size\_t in\_size)

Constructs of a CInputVector from a memory address and a given number of elements

const *T* \***CInputVector::data**() const

returns the start address of the data captured by this CInputVector

size\_t **CInputVector::size**() const

returns the number of elements captured by this CInputVector

### 1.1.3 API-Classes

#### CAccessRight

class Lib3MF::CAccessRight : public CBase

*PConsumer* **GetConsumer**()

Gets the consumer associated with this access right

**Returns** The consumer instance

eWrappingAlgorithm **GetWrappingAlgorithm**()

Gets the associated encryption algorithm

**Returns** The algorithm used for the key in this accessright

eMgfAlgorithm **GetMgfAlgorithm**()

Gets the associated mask generation function algorithm

**Returns** The MFG1 algorithm

eDigestMethod **GetDigestMethod**()

Gets the digest method assoicated

**Returns** The digest method for this accessright

typedef std::shared\_ptr<*CAccessRight*> Lib3MF::PAccessRight

Shared pointer to CAccessRight to easily allow reference counting.

#### CAttachment

class Lib3MF::CAttachment : public CBase

std::string **GetPath**()

Retrieves an attachment's package path. This function will be removed in a later release.

**Returns** returns the attachment's package path string

void **SetPath**(const std::string &sPath)

Sets an attachment's package path. This function will be removed in a later release.

**Parameters** *sPath* – new path of the attachment.

***PPackagePart* PackagePart()**

Returns the PackagePart that is this attachment.

**Returns** The PackagePart of this attachment.

**std::string GetRelationshipType()**

Retrieves an attachment's relationship type

**Returns** returns the attachment's package relationship type string

**void SetRelationshipType(const std::string &sPath)**

Sets an attachment's relationship type.

**Parameters** **sPath** – new relationship type string.

**void WriteToFile(const std::string &sFileName)**

Writes out the attachment as file.

**Parameters** **sFileName** – file to write into.

**void ReadFromFile(const std::string &sFileName)**

Reads an attachment from a file.

**Parameters** **sFileName** – file to read from.

***Lib3MF\_uint64* GetStreamSize()**

Retrieves the size of the attachment stream

**Returns** the stream size

**void WriteToBuffer(std::vector<*Lib3MF\_uint8*> &BufferBuffer)**

Writes out the attachment into a buffer

**Parameters** **BufferBuffer** – Buffer to write into

**void ReadFromBuffer(const *CInputVector*<*Lib3MF\_uint8*> &BufferBuffer)**

Reads an attachment from a memory buffer

**Parameters** **BufferBuffer** – Buffer to read from

**typedef std::shared\_ptr<*CAttachment*> Lib3MF::PAttachment**

Shared pointer to CAttachment to easily allow reference counting.

**CBase**

**class Lib3MF::CBase**

**typedef std::shared\_ptr<*CBase*> Lib3MF::PBase**

Shared pointer to CBase to easily allow reference counting.

**CBaseMaterialGroup**

**class Lib3MF::CBaseMaterialGroup : public *CResource***

The BaseMaterialGroup corresponds to a basematerials-element within a 3MF document

***Lib3MF\_uint32* GetCount()**

Retrieves the count of base materials in the material group.

**Returns** returns the count of base materials.

**void GetAllPropertyIDs(std::vector<*Lib3MF\_uint32*> &PropertyIDsBuffer)**

returns all the PropertyIDs of all materials in this group

**Parameters** **PropertyIDsBuffer** – PropertyID of the material in the material group.

*Lib3MF\_uint32* **AddMaterial**(const std::string &sName, const *sColor* &DisplayColor)

Adds a new material to the material group

**Parameters**

- **sName** – new name of the base material.
- **DisplayColor** – Display color of the material

**Returns** returns new PropertyID of the new material in the material group.

void **RemoveMaterial**(const *Lib3MF\_uint32* nPropertyID)

Removes a material from the material group.

**Parameters** **nPropertyID** – PropertyID of the material in the material group.

std::string **GetName**(const *Lib3MF\_uint32* nPropertyID)

Returns the base material's name

**Parameters** **nPropertyID** – PropertyID of the material in the material group.

**Returns** returns the name of the base material.

void **SetName**(const *Lib3MF\_uint32* nPropertyID, const std::string &sName)

Sets a base material's name

**Parameters**

- **nPropertyID** – PropertyID of the material in the material group.
- **sName** – new name of the base material.

void **SetDisplayColor**(const *Lib3MF\_uint32* nPropertyID, const *sColor* &TheColor)

Sets a base material's display color.

**Parameters**

- **nPropertyID** – PropertyID of the material in the material group.
- **TheColor** – The base material's display color

*sColor* **GetDisplayColor**(const *Lib3MF\_uint32* nPropertyID)

Returns a base material's display color.

**Parameters** **nPropertyID** – PropertyID of the material in the material group.

**Returns** The base material's display color

typedef std::shared\_ptr<*CBaseMaterialGroup*> Lib3MF::PBaseMaterialGroup

Shared pointer to CBaseMaterialGroup to easily allow reference counting.

## CBaseMaterialGroupIterator

class Lib3MF::CBaseMaterialGroupIterator : public *CResourceIterator*

*PBaseMaterialGroup* **GetCurrentBaseMaterialGroup**()

Returns the MaterialGroup the iterator points at.

**Returns** returns the BaseMaterialGroup instance.

typedef std::shared\_ptr<*CBaseMaterialGroupIterator*> Lib3MF::PBaseMaterialGroupIterator

Shared pointer to CBaseMaterialGroupIterator to easily allow reference counting.

## CBeamLattice

class Lib3MF::CBeamLattice : public CBase

*Lib3MF\_double* GetMinLength()

Returns the minimal length of beams for the beamlattice.

**Returns** minimal length of beams for the beamlattice

void SetMinLength(const *Lib3MF\_double* dMinLength)

Sets the minimal length of beams for the beamlattice.

**Parameters** **dMinLength** – minimal length of beams for the beamlattice

void GetClipping(*eBeamLatticeClipMode* &eClipMode, *Lib3MF\_uint32* &nUniqueResourceID)

Returns the clipping mode and the clipping-mesh for the beamlattice of this mesh.

**Parameters**

- **eClipMode** – contains the clip mode of this mesh
- **nUniqueResourceID** – filled with the UniqueResourceID of the clipping mesh-object or an undefined value if pClipMode is MODELBEAMLATTICECLIP-MODE\_NONE

void SetClipping(const *eBeamLatticeClipMode* eClipMode, const *Lib3MF\_uint32* nUniqueResourceID)

Sets the clipping mode and the clipping-mesh for the beamlattice of this mesh.

**Parameters**

- **eClipMode** – contains the clip mode of this mesh
- **nUniqueResourceID** – the UniqueResourceID of the clipping mesh-object. This mesh-object has to be defined before setting the Clipping.

bool GetRepresentation(*Lib3MF\_uint32* &nUniqueResourceID)

Returns the representation-mesh for the beamlattice of this mesh.

**Returns** flag whether the beamlattice has a representation mesh.

**Parameters** **nUniqueResourceID** – filled with the UniqueResourceID of the clipping mesh-object.

void SetRepresentation(const *Lib3MF\_uint32* nUniqueResourceID)

Sets the representation-mesh for the beamlattice of this mesh.

**Parameters** **nUniqueResourceID** – the UniqueResourceID of the representation mesh-object. This mesh-object has to be defined before setting the representation.

void GetBallOptions(*eBeamLatticeBallMode* &eBallMode, *Lib3MF\_double* &dBallRadius)

Returns the ball mode and the default ball radius for the beamlattice of this mesh. Returns the ball mode and the default ball radius for the beamlattice of this mesh.

**param eBallMode** contains the ball mode of this mesh

**param dBallRadius** default ball radius of balls for the beamlattice

typedef std::shared\_ptr<*CBeamLattice*> Lib3MF::PBeamLattice

Shared pointer to CBeamLattice to easily allow reference counting.

## CBeamSet

class Lib3MF::CBeamSet : public CBase

void **SetName**(const std::string &sName)

Sets a beamset's name string

**Parameters** **sName** – new name of the beamset.

std::string **GetName**()

Retrieves a beamset's name string

**Returns** returns the name of the beamset.

void **SetIdentifier**(const std::string &sIdentifier)

Sets a beamset's identifier string

**Parameters** **sIdentifier** – new name of the beamset.

std::string **GetIdentifier**()

Retrieves a beamset's identifier string

**Returns** returns the identifier of the beamset.

*Lib3MF\_uint32* **GetReferenceCount**()

Retrieves the reference count of a beamset

**Returns** returns the reference count

void **SetReferences**(const *CInputVector*<*Lib3MF\_uint32*> &ReferencesBuffer)

Sets the references of a beamset

**Parameters** **ReferencesBuffer** – the new indices of all beams in this beamset

void **GetReferences**(std::vector<*Lib3MF\_uint32*> &ReferencesBuffer)

Retrieves the references of a beamset

**Parameters** **ReferencesBuffer** – retrieves the indices of all beams in this beamset

*Lib3MF\_uint32* **GetBallReferenceCount**()

Retrieves the ball reference count of a beamset

**Returns** returns the ball reference count

void **SetBallReferences**(const *CInputVector*<*Lib3MF\_uint32*> &BallReferencesBuffer)

Sets the ball references of a beamset

**Parameters** **BallReferencesBuffer** – the new indices of all balls in this beamset

void **GetBallReferences**(std::vector<*Lib3MF\_uint32*> &BallReferencesBuffer)

Retrieves the ball references of a beamset

**Parameters** **BallReferencesBuffer** – retrieves the indices of all balls in this beamset

typedef std::shared\_ptr<*CBeamSet*> Lib3MF::PBeamSet

Shared pointer to CBeamSet to easily allow reference counting.



**CBuildItem**

```
class Lib3MF::CBuildItem : public CBase
```

*PObject* **GetObjectResource()**

Retrieves the object resource associated to a build item

**Returns** returns the associated resource instance

std::string **GetUUID**(bool &bHasUUID)

returns, whether a build item has a UUID and, if true, the build item's UUID

**Parameters** **bHasUUID** – flag whether the build item has a UUID

**Returns** the UUID as string of the form 'xxxxxxxx-xxxx-xxxx-xxxxxxxxxxxxxxxx'

void **SetUUID**(const std::string &sUUID)

sets the build item's UUID

**Parameters** **sUUID** – the UUID as string of the form 'xxxxxxxx-xxxx-xxxx-xxxxxxxxxxxxxxxx'

*Lib3MF\_uint32* **GetObjectResourceID**()

Retrieves the object UniqueResourceID associated to a build item

**Returns** returns the UniqueResourceID of the object

bool **HasObjectTransform**()

Checks, if a build item has a non-identity transformation matrix

**Returns** returns true, if the transformation matrix is not the identity

*sTransform* **GetObjectTransform**()

Retrieves a build item's transformation matrix.

**Returns** returns the transformation matrix

void **SetObjectTransform**(const *sTransform* &Transform)

Sets a build item's transformation matrix.

**Parameters** **Transform** – new transformation matrix

std::string **GetPartNumber**()

Retrieves a build item's part number string

**Returns** Returns a build item's part number string

void **SetPartNumber**(const std::string &sSetPartnumber)

Sets a build item's part number string

**Parameters** **sSetPartnumber** – new part number string for referencing parts from the outside world

*PMetaDataGroup* **GetMetaDataGroup**()

Returns the metadatagroup of this build item

**Returns** returns an Instance of the metadatagroup of this build item

*sBox* **GetOutbox**()

Returns the outbox of a build item

**Returns** Outbox of this build item

```
typedef std::shared_ptr<CBuildItem> Lib3MF::PBuildItem
```

Shared pointer to CBuildItem to easily allow reference counting.

## CBuildItemIterator

class Lib3MF::CBuildItemIterator : public CBase

bool **MoveNext()**

Iterates to the next build item in the list.

**Returns** Iterates to the next build item in the list.

bool **MovePrevious()**

Iterates to the previous build item in the list.

**Returns** Iterates to the previous build item in the list.

PBuildItem **GetCurrent()**

Returns the build item the iterator points at.

**Returns** returns the build item instance.

PBuildItemIterator **Clone()**

Creates a new build item iterator with the same build item list.

**Returns** returns the cloned Iterator instance

Lib3MF\_uint64 **Count()**

Returns the number of build items the iterator captures.

**Returns** returns the number of build items the iterator captures.

typedef std::shared\_ptr<CBuildItemIterator> Lib3MF::PBuildItemIterator

Shared pointer to CBuildItemIterator to easily allow reference counting.

## CColorGroup

class Lib3MF::CColorGroup : public CResource

Lib3MF\_uint32 **GetCount()**

Retrieves the count of base materials in this Color Group.

**Returns** returns the count of colors within this color group.

void **GetAllPropertyIDs**(std::vector<Lib3MF\_uint32> &PropertyIDsBuffer)

returns all the PropertyIDs of all colors within this group

**Parameters** **PropertyIDsBuffer** – PropertyID of the color in the color group.

Lib3MF\_uint32 **AddColor**(const sColor &TheColor)

Adds a new value.

**Parameters** **TheColor** – The new color

**Returns** PropertyID of the new color within this color group.

void **RemoveColor**(const Lib3MF\_uint32 nPropertyID)

Removes a color from the color group.

**Parameters** **nPropertyID** – PropertyID of the color to be removed from the color group.

void **SetColor**(const Lib3MF\_uint32 nPropertyID, const sColor &TheColor)

Sets a color value.

**Parameters**

- **nPropertyID** – PropertyID of a color within this color group.
- **TheColor** – The color

*sColor* **GetColor**(const *Lib3MF\_uint32* nPropertyID)

Sets a color value.

**Parameters** **nPropertyID** – PropertyID of a color within this color group.

**Returns** The color

typedef std::shared\_ptr<*CColorGroup*> **Lib3MF::PColorGroup**

Shared pointer to CColorGroup to easily allow reference counting.

## CColorGroupIterator

class **Lib3MF::CColorGroupIterator** : public *CResourceIterator*

*PColorGroup* **GetCurrentColorGroup**()

Returns the ColorGroup the iterator points at.

**Returns** returns the ColorGroup instance.

typedef std::shared\_ptr<*CColorGroupIterator*> **Lib3MF::PColorGroupIterator**

Shared pointer to CColorGroupIterator to easily allow reference counting.

## CComponent

class **Lib3MF::CComponent** : public *CBase*

*PObject* **GetObjectResource**()

Returns the Resource Instance of the component.

**Returns** filled with the Resource Instance.

*Lib3MF\_uint32* **GetObjectResourceID**()

Returns the UniqueResourceID of the component.

**Returns** returns the UniqueResourceID.

std::string **GetUUID**(bool &bHasUUID)

returns, whether a component has a UUID and, if true, the component's UUID

**Parameters** **bHasUUID** – flag whether the component has a UUID

**Returns** the UUID as string of the form 'xxxxxxxx-xxxx-xxxx-xxxxxxxxxxxxxxxx'

void **SetUUID**(const std::string &sUUID)

sets the component's UUID

**Parameters** **sUUID** – the UUID as string of the form 'xxxxxxxx-xxxx-xxxx-xxxxxxxxxxxxxxxx'

bool **HasTransform**()

Returns, if the component has a different transformation than the identity matrix

**Returns** if true is returned, the transformation is not equal than the identity

*sTransform* **GetTransform**()

Returns the transformation matrix of the component.

**Returns** filled with the component transformation matrix

void **SetTransform**(const *sTransform* &Transform)  
Sets the transformation matrix of the component.

**Parameters** **Transform** – new transformation matrix

typedef std::shared\_ptr<*CComponent*> Lib3MF::PComponent  
Shared pointer to CComponent to easily allow reference counting.

## CComponentsObject

class Lib3MF::CComponentsObject : public *CObject*

*PComponent* **AddComponent**(*CObject* \*pObjectResource, const *sTransform* &Transform)  
Adds a new component to a components object.

**Parameters**

- **pObjectResource** – object to add as component. Must not lead to circular references!
- **Transform** – optional transform matrix for the component.

**Returns** new component instance

*PComponent* **GetComponent**(const *Lib3MF\_uint32* nIndex)  
Retrieves a component from a component object.

**Parameters** **nIndex** – index of the component to retrieve (0 to componentcount - 1)

**Returns** component instance

*Lib3MF\_uint32* **GetComponentCount**()  
Retrieves a component count of a component object.

**Returns** returns the component count

typedef std::shared\_ptr<*CComponentsObject*> Lib3MF::PComponentsObject  
Shared pointer to CComponentsObject to easily allow reference counting.

## CComponentsObjectIterator

class Lib3MF::CComponentsObjectIterator : public *CResourceIterator*

*PComponentsObject* **GetCurrentComponentsObject**()  
Returns the ComponentsObject the iterator points at.

**Returns** returns the ComponentsObject instance.

typedef std::shared\_ptr<*CComponentsObjectIterator*> Lib3MF::PComponentsObjectIterator  
Shared pointer to CComponentsObjectIterator to easily allow reference counting.

## CCompositeMaterials

class Lib3MF::CCompositeMaterials : public CResource

*Lib3MF\_uint32* GetCount()

Retrieves the count of Composite-s in the CompositeMaterials.

**Returns** returns the count of Composite-s

void GetAllPropertyIDs(std::vector<*Lib3MF\_uint32*> &PropertyIDsBuffer)

returns all the PropertyIDs of all Composite-Mixing Values in this CompositeMaterials

**Parameters** **PropertyIDsBuffer** – PropertyID of the Composite-Mixing Values in the CompositeMaterials.

*PBaseMaterialGroup* GetBaseMaterialGroup()

Obtains the BaseMaterialGroup instance of this CompositeMaterials.

**Returns** returns the BaseMaterialGroup instance of this CompositeMaterials

*Lib3MF\_uint32* AddComposite(const *CInputVector<sCompositeConstituent>* &CompositeBuffer)

Adds a new Composite-Mixing Values to the CompositeMaterials.

**Parameters** **CompositeBuffer** – The Composite Constituents to be added as composite

**Returns** returns new PropertyID of the new Composite in the CompositeMaterials.

void RemoveComposite(const *Lib3MF\_uint32* nPropertyID)

Removes a Composite-Maxing Ratio from the CompositeMaterials.

**Parameters** **nPropertyID** – PropertyID of the Composite-Mixing Values in the CompositeMaterials to be removed.

void GetComposite(const *Lib3MF\_uint32* nPropertyID, std::vector<*sCompositeConstituent*> &CompositeBuffer)

Obtains a Composite-Maxing Ratio of this CompositeMaterials.

**Parameters**

- **nPropertyID** – the PropertyID of the Composite-Maxing Ratio in the CompositeMaterials.
- **CompositeBuffer** – The Composite-Mixing Values with the given PropertyID

typedef std::shared\_ptr<*CCompositeMaterials*> Lib3MF::PCompositeMaterials

Shared pointer to CCompositeMaterials to easily allow reference counting.

## CCompositeMaterialsIterator

class Lib3MF::CCompositeMaterialsIterator : public CResourceIterator

*PCompositeMaterials* GetCurrentCompositeMaterials()

Returns the CompositeMaterials the iterator points at.

**Returns** returns the CompositeMaterials instance.

typedef std::shared\_ptr<*CCompositeMaterialsIterator*> Lib3MF::PCompositeMaterialsIterator

Shared pointer to CCompositeMaterialsIterator to easily allow reference counting.

## CConsumer

class Lib3MF::CConsumer : public CBase

std::string GetConsumerID()

Gets the consumerid

**Returns** A unique identifier for the consumers

std::string GetKeyID()

Getts the keyid

**Returns** The identifier for the key of this consumer

std::string GetKeyValue()

Gets the keyvalue associated with this consumer

**Returns** The public key, when available, of this consumer

typedef std::shared\_ptr<CConsumer> Lib3MF::PConsumer

Shared pointer to CConsumer to easily allow reference counting.

## CContentEncryptionParams

class Lib3MF::CContentEncryptionParams : public CBase

eEncryptionAlgorithm GetEncryptionAlgorithm()

Returns the encryption method to be used in this encryption process

**Returns**

void GetKey(std::vector<Lib3MF\_uint8> &ByteDataBuffer)

Gets the key for the resource associated

**Parameters** ByteDataBuffer – Pointer to a buffer where to place the key.

void GetInitializationVector(std::vector<Lib3MF\_uint8> &ByteDataBuffer)

Gets the IV data

**Parameters** ByteDataBuffer – Pointer to a buffer where to place the data.

void GetAuthenticationTag(std::vector<Lib3MF\_uint8> &ByteDataBuffer)

A handler descriptor that uniquely identifies the context of the resource. Each resource will be assigned a different value

**Parameters** ByteDataBuffer – Pointer to a buffer where to place the data.

void SetAuthenticationTag(const CInputVector<Lib3MF\_uint8> &ByteDataBuffer)

Sets the authentication tag

**Parameters** ByteDataBuffer – The authentication tag size

void GetAdditionalAuthenticationData(std::vector<Lib3MF\_uint8> &ByteDataBuffer)

A handler descriptor that uniquely identifies the context of the resource. Each resource will be assigned a different value

**Parameters** ByteDataBuffer – Buffer where the data will be placed

Lib3MF\_uint64 GetDescriptor()

A handler descriptor that uniquely identifies the context of the resource. Each resource will be assigned a different value

**Returns**

std::string **GetKeyUUID()**

Gets the resourcedatagroup keyuuid

**Returns** The resourcedatagroup keyuuid that may be use to reference an external key

typedef std::shared\_ptr<*CContentEncryptionParams*> Lib3MF::PContentEncryptionParams

Shared pointer to CContentEncryptionParams to easily allow reference counting.

**CKeyStore**

class Lib3MF::CKeyStore : public CBase

*PConsumer* **AddConsumer**(const std::string &sConsumerID, const std::string &sKeyID, const std::string &sKeyValue)

Adds a consumer to the keystore

**Parameters**

- **sConsumerID** – A unique identifier for the consumer
- **sKeyID** – The id of the key of the consumer
- **sKeyValue** – The public key for this consumer in PEM format

**Returns** The consumer instance

*Lib3MF\_uint64* **GetConsumerCount()**

Gets the number of consumers in the keystore

**Returns** The consumer count

*PConsumer* **GetConsumer**(const *Lib3MF\_uint64* nConsumerIndex)

Get a consumer from the keystore

**Parameters** **nConsumerIndex** – The index of the consumer

**Returns** The consumer instance

void **RemoveConsumer**(*CConsumer* \*pConsumer)

Removes a consumer from the keystore

**Parameters** **pConsumer** – The consumer instance to remove

*PConsumer* **FindConsumer**(const std::string &sConsumerID)

Finds a consumer by ID

**Parameters** **sConsumerID** – The ID of the consumer

**Returns** The consumer instance

*Lib3MF\_uint64* **GetResourceDataGroupCount()**

Gets the number of resource data group in the keystore

**Returns** The number of resource data available

*PResourceDataGroup* **AddResourceDataGroup()**

Adds a resource data group into the keystore.

**Returns** The resource data group instance

*PResourceDataGroup* **GetResourceDataGroup**(const *Lib3MF\_uint64* nResourceDataIndex)

Gets a resource data group

**Parameters** **nResourceDataIndex** – The index of the resource data

**Returns** The resource data group instance

void **RemoveResourceDataGroup**(*CResourceDataGroup* \*pResourceDataGroup)

Removes a resource data group

**Parameters** **pResourceDataGroup** – The resource data group instance

*PResourceDataGroup* **FindResourceDataGroup**(*CPackagePart* \*pPartPath)

Finds a resource data group that contains a particular resourcedata

**Parameters** **pPartPath** – The target path for the resourcedata hold by the resource data group

**Returns** The data resource instance

*PResourceData* **AddResourceData**(*CResourceDataGroup* \*pResourceDataGroup, *CPackagePart* \*pPartPath, const eEncryptionAlgorithm eAlgorithm, const *eCompression* eCompression, const *CInputVector*<Lib3MF\_uint8> &AdditionalAuthenticationDataBuffer)

Add resourcedata to resourcedatagroup element

**Parameters**

- **pResourceDataGroup** – The resource data group where to add this resource data
- **pPartPath** – The path of the part to be encrypted
- **eAlgorithm** – The encryption algorithm to be used to encrypt this resource
- **eCompression** – Whether compression should be used prior to encryption
- **AdditionalAuthenticationDataBuffer** – Additional data to be encrypted along the contents for better security

**Returns** The data resource instance

void **RemoveResourceData**(*CResourceData* \*pResourceData)

Removes a resource data

**Parameters** **pResourceData** – The resource data to be removed

*PResourceData* **FindResourceData**(*CPackagePart* \*pResourcePath)

Finds a resource data on this resource group

**Parameters** **pResourcePath** – The target path for the resourcedata

**Returns** The resource data instance

*Lib3MF\_uint64* **GetResourceDataCount**()

Gets the number of resource data in the keystore

**Returns** The number of resource data available

*PResourceData* **GetResourceData**(const *Lib3MF\_uint64* nResourceDataIndex)

Gets a resource data

**Parameters** **nResourceDataIndex** – The index of the resource data

**Returns** The data resource instance

std::string **GetUUID**(bool &bHasUUID)

Gets the keystore UUID

**Parameters** **bHasUUID** – flag whether the keystore has a UUID

**Returns** returns the keystore uuid.



void **SetUUID**(const std::string &sUUID)  
Sets the keystore UUID

**Parameters** **sUUID** – The new keystore uuid.

typedef std::shared\_ptr<*CKeyStore*> Lib3MF::PKeyStore  
Shared pointer to CKeyStore to easily allow reference counting.

## CMeshObject

class Lib3MF::CMeshObject : public CObject

*Lib3MF\_uint32* **GetVertexCount**()

Returns the vertex count of a mesh object.

**Returns** filled with the vertex count.

*Lib3MF\_uint32* **GetTriangleCount**()

Returns the triangle count of a mesh object.

**Returns** filled with the triangle count.

*sPosition* **GetVertex**(const *Lib3MF\_uint32* nIndex)

Returns the vertex count of a mesh object.

**Parameters** **nIndex** – Index of the vertex (0 to vertexcount - 1)

**Returns** filled with the vertex coordinates.

void **SetVertex**(const *Lib3MF\_uint32* nIndex, const *sPosition* &Coordinates)

Sets the coordinates of a single vertex of a mesh object

**Parameters**

- **nIndex** – Index of the vertex (0 to vertexcount - 1)
- **Coordinates** – contains the vertex coordinates.

*Lib3MF\_uint32* **AddVertex**(const *sPosition* &Coordinates)

Adds a single vertex to a mesh object

**Parameters** **Coordinates** – contains the vertex coordinates.

**Returns** Index of the new vertex

void **GetVertices**(std::vector<*sPosition*> &VerticesBuffer)

Obtains all vertex positions of a mesh object

**Parameters** **VerticesBuffer** – contains the vertex coordinates.

*sTriangle* **GetTriangle**(const *Lib3MF\_uint32* nIndex)

Returns indices of a single triangle of a mesh object.

**Parameters** **nIndex** – Index of the triangle (0 to trianglecount - 1)

**Returns** filled with the triangle indices.

void **SetTriangle**(const *Lib3MF\_uint32* nIndex, const *sTriangle* &Indices)

Sets the indices of a single triangle of a mesh object.

**Parameters**

- **nIndex** – Index of the triangle (0 to trianglecount - 1)
- **Indices** – contains the triangle indices.

*Lib3MF\_uint32* **AddTriangle**(const *sTriangle* &Indices)

Adds a single triangle to a mesh object

**Parameters** **Indices** – contains the triangle indices.

**Returns** Index of the new triangle

void **GetTriangleIndices**(std::vector<*sTriangle*> &IndicesBuffer)

Get all triangles of a mesh object

**Parameters** **IndicesBuffer** – contains the triangle indices.

void **SetObjectLevelProperty**(const *Lib3MF\_uint32* nUniqueResourceID, const *Lib3MF\_uint32* nPropertyID)

Sets the property at the object-level of the mesh object.

**Parameters**

- **nUniqueResourceID** – the object-level Property UniqueResourceID.
- **nPropertyID** – the object-level PropertyID.

bool **GetObjectLevelProperty**(*Lib3MF\_uint32* &nUniqueResourceID, *Lib3MF\_uint32* &nPropertyID)

Gets the property at the object-level of the mesh object.

**Parameters**

- **nUniqueResourceID** – the object-level Property UniqueResourceID.
- **nPropertyID** – the object-level PropertyID.

**Returns** Has an object-level property been specified?

void **SetTriangleProperties**(const *Lib3MF\_uint32* nIndex, const *sTriangleProperties* &Properties)

Sets the properties of a single triangle of a mesh object.

**Parameters**

- **nIndex** – Index of the triangle (0 to trianglecount - 1)
- **Properties** – contains the triangle properties.

void **GetTriangleProperties**(const *Lib3MF\_uint32* nIndex, *sTriangleProperties* &Property)

Gets the properties of a single triangle of a mesh object.

**Parameters**

- **nIndex** – Index of the triangle (0 to trianglecount - 1)
- **Property** – returns the triangle properties.

void **SetAllTriangleProperties**(const *CInputVector*<*sTriangleProperties*> &PropertiesArrayBuffer)

Sets the properties of all triangles of a mesh object. Sets the object level property to the first entry of the passed triangle properties, if not yet specified.

**Parameters** **PropertiesArrayBuffer** – contains the triangle properties array. Must have trianglecount elements.

void **GetAllTriangleProperties**(std::vector<*sTriangleProperties*> &PropertiesArrayBuffer)

Gets the properties of all triangles of a mesh object.

**Parameters** **PropertiesArrayBuffer** – returns the triangle properties array. Must have trianglecount elements.

void **ClearAllProperties**()

Clears all properties of this mesh object (triangle and object-level).

```
void SetGeometry(const CInputVector<sPosition> &VerticesBuffer, const CInputVector<sTriangle>
    &IndicesBuffer)
```

Set all triangles of a mesh object

#### Parameters

- **VerticesBuffer** – contains the positions.
- **IndicesBuffer** – contains the triangle indices.

```
bool IsManifoldAndOriented()
```

Retrieves, if an object describes a topologically oriented and manifold mesh, according to the core spec.

**Returns** returns, if the object is oriented and manifold.

```
PBeamLattice BeamLattice()
```

Retrieves the BeamLattice within this MeshObject.

**Returns** the BeamLattice within this MeshObject

```
typedef std::shared_ptr<CMeshObject> Lib3MF::PMeshObject
```

Shared pointer to CMeshObject to easily allow reference counting.

## CMeshObjectIterator

```
class Lib3MF::CMeshObjectIterator : public CResourceIterator
```

```
PMeshObject GetCurrentMeshObject()
```

Returns the MeshObject the iterator points at.

**Returns** returns the MeshObject instance.

```
typedef std::shared_ptr<CMeshObjectIterator> Lib3MF::PMeshObjectIterator
```

Shared pointer to CMeshObjectIterator to easily allow reference counting.

## CMetaData

```
class Lib3MF::CMetaData : public CBase
```

```
std::string GetNamespace()
```

returns the namespace URL of the metadata

**Returns** the namespace URL of the metadata

```
void SetNamespace(const std::string &sNamespace)
```

sets a new namespace URL of the metadata

**Parameters** **sNamespace** – the new namespace URL of the metadata

```
std::string GetName()
```

returns the name of a metadata

**Returns** the name of the metadata

```
void SetName(const std::string &sName)
```

sets a new name of a metadata

**Parameters** **sName** – the new name of the metadata

```
std::string GetKey()
```

returns the (namespace+name) of a metadata

**Returns** the key (namespace+name) of the metadata

bool **GetMustPreserve**()

returns, whether a metadata must be preserved

**Returns** returns, whether a metadata must be preserved

void **SetMustPreserve**(const bool bMustPreserve)

sets whether a metadata must be preserved

**Parameters** **bMustPreserve** – a new value whether a metadata must be preserved

std::string **GetType**()

returns the type of a metadata

**Returns** the type of the metadata

void **SetType**(const std::string &sType)

sets a new type of a metadata. This must be a simple XML type

**Parameters** **sType** – a new type of the metadata

std::string **GetValue**()

returns the value of the metadata

**Returns** the value of the metadata

void **SetValue**(const std::string &sValue)

sets a new value of the metadata

**Parameters** **sValue** – a new value of the metadata

typedef std::shared\_ptr<*CMetaData*> Lib3MF::P**MetaData**

Shared pointer to CMetaData to easily allow reference counting.

## CMetaDataGroup

class Lib3MF::CMetaDataGroup : public *CBase*

*Lib3MF\_uint32* **GetMetaDataCount**()

returns the number of metadata in this metadatagroup

**Returns** returns the number metadata

*PMetaData* **GetMetaData**(const *Lib3MF\_uint32* nIndex)

returns a metadata value within this metadatagroup

**Parameters** **nIndex** – Index of the Metadata.

**Returns** an instance of the metadata

*PMetaData* **GetMetaDataByKey**(const std::string &sNameSpace, const std::string &sName)

returns a metadata value within this metadatagroup

**Parameters**

- **sNameSpace** – the namespace of the metadata
- **sName** – the name of the Metadata

**Returns** an instance of the metadata

void **RemoveMetaDataByIndex**(const *Lib3MF\_uint32* nIndex)

removes metadata by index from the model.

**Parameters** **nIndex** – Index of the metadata to remove

void **RemoveMetaData**(*CMetaData* \*pTheMetaData)  
removes metadata from the model.

**Parameters** **pTheMetaData** – The metadata to remove

*PMetaData* **AddMetaData**(const std::string &sNameSpace, const std::string &sName, const std::string &sValue, const std::string &sType, const bool bMustPreserve)  
adds a new metadata to this metadata group

**Parameters**

- **sNameSpace** – the namespace of the metadata
- **sName** – the name of the metadata
- **sValue** – the value of the metadata
- **sType** – the type of the metadata
- **bMustPreserve** – should the metadata be preserved

**Returns** a new instance of the metadata

typedef std::shared\_ptr<*CMetaDataGroup*> Lib3MF::P**MetaDataGroup**  
Shared pointer to CMetaDataGroup to easily allow reference counting.

## CModel

class Lib3MF::C**Model** : public *CBase*

*PPackagePart* **RootModelPart**()

Returns the PackagePart within the OPC package that holds the root model.

**Returns** the PackagePart within the OPC package that holds the model-file

*PPackagePart* **FindOrCreatePackagePart**(const std::string &sAbsolutePath)

Returns a new PackagePart for use within the OPC package.

**Parameters** **sAbsolutePath** – the absolute Path (physical location) within the OPC package

**Returns** the new PackagePart within the OPC package

void **SetUnit**(const *eModelUnit* eUnit)  
sets the units of a model.

**Parameters** **eUnit** – Unit enum value for the model unit

*eModelUnit* **GetUnit**()

returns the units of a model.

**Returns** Unit enum value for the model unit

std::string **GetLanguage**()  
retrieves the language of a model

**Returns** language identifier

void **SetLanguage**(const std::string &sLanguage)  
sets the language of a model

**Parameters** **sLanguage** – language identifier

*PWriter* **QueryWriter**(const std::string &sWriterClass)  
creates a model writer instance for a specific file type

**Parameters** **sWriterClass** – string identifier for the file type

**Returns** string identifier for the file type

*PReader* **QueryReader**(const std::string &sReaderClass)  
creates a model reader instance for a specific file type

**Parameters** **sReaderClass** – string identifier for the file type

**Returns** string identifier for the file type

*PTexture2D* **GetTexture2DByID**(const *Lib3MF\_uint32* nUniqueResourceID)  
finds a model texture by its UniqueResourceID

**Parameters** **nUniqueResourceID** – UniqueResourceID

**Returns** returns the texture2d instance

*ePropertyType* **GetPropertyTypeByID**(const *Lib3MF\_uint32* nUniqueResourceID)  
returns a Property's type

**Parameters** **nUniqueResourceID** – Resource ID of the Property to Query

**Returns** returns a Property's type

*PBaseMaterialGroup* **GetBaseMaterialGroupByID**(const *Lib3MF\_uint32* nUniqueResourceID)  
finds a model base material group by its UniqueResourceID

**Parameters** **nUniqueResourceID** – UniqueResourceID

**Returns** returns the BaseMaterialGroup instance

*PTexture2DGroup* **GetTexture2DGroupByID**(const *Lib3MF\_uint32* nUniqueResourceID)  
finds a model texture2d group by its UniqueResourceID

**Parameters** **nUniqueResourceID** – UniqueResourceID

**Returns** returns the Texture2DGroup instance

*PCompositeMaterials* **GetCompositeMaterialsByID**(const *Lib3MF\_uint32* nUniqueResourceID)  
finds a model CompositeMaterials by its UniqueResourceID

**Parameters** **nUniqueResourceID** – UniqueResourceID

**Returns** returns the CompositeMaterials instance

*PMultiPropertyGroup* **GetMultiPropertyGroupByID**(const *Lib3MF\_uint32* nUniqueResourceID)  
finds a model MultiPropertyGroup by its UniqueResourceID

**Parameters** **nUniqueResourceID** – UniqueResourceID

**Returns** returns the MultiPropertyGroup instance

*PMeshObject* **GetMeshObjectByID**(const *Lib3MF\_uint32* nUniqueResourceID)  
finds a mesh object by its UniqueResourceID

**Parameters** **nUniqueResourceID** – UniqueResourceID

**Returns** returns the mesh object instance

*PComponentsObject* **GetComponentsObjectByID**(const *Lib3MF\_uint32* nUniqueResourceID)  
finds a components object by its UniqueResourceID

**Parameters** **nUniqueResourceID** – UniqueResourceID

**Returns** returns the components object instance

*PColorGroup* **GetColorGroupByID**(const *Lib3MF\_uint32* nUniqueResourceID)  
finds a model color group by its UniqueResourceID

**Parameters** *nUniqueResourceID* – UniqueResourceID

**Returns** returns the ColorGroup instance

*PSliceStack* **GetSliceStackByID**(const *Lib3MF\_uint32* nUniqueResourceID)  
finds a model slicestack by its UniqueResourceID

**Parameters** *nUniqueResourceID* – UniqueResourceID

**Returns** returns the slicestack instance

std::string **GetBuildUUID**(bool &bHasUUID)  
returns, whether a build has a UUID and, if true, the build's UUID

**Parameters** *bHasUUID* – flag whether the build has a UUID

**Returns** the UUID as string of the form 'xxxxxxxx-xxxx-xxxx-xxxxxxxxxxxxxxxx'

void **SetBuildUUID**(const std::string &sUUID)  
sets the build's UUID

**Parameters** *sUUID* – the UUID as string of the form 'xxxxxxxx-xxxx-xxxx-xxxxxxxxxxxxxxxx'

*PBuildItemIterator* **GetBuildItems**()  
creates a build item iterator instance with all build items.

**Returns** returns the iterator instance.

*sBox* **GetOutbox**()  
Returns the outbox of a Model

**Returns** Outbox of this Model

*PResourceIterator* **GetResources**()  
creates a resource iterator instance with all resources.

**Returns** returns the iterator instance.

*PObjectIterator* **GetObjects**()  
creates a resource iterator instance with all object resources.

**Returns** returns the iterator instance.

*PMeshObjectIterator* **GetMeshObjects**()  
creates a resource iterator instance with all mesh object resources.

**Returns** returns the iterator instance.

*PComponentsObjectIterator* **GetComponentsObjects**()  
creates a resource iterator instance with all components object resources.

**Returns** returns the iterator instance.

*PTexture2DIterator* **GetTexture2Ds**()  
creates a Texture2DIterator instance with all texture2d resources.

**Returns** returns the iterator instance.

*PBaseMaterialGroupIterator* **GetBaseMaterialGroups**()  
creates a BaseMaterialGroupIterator instance with all base material resources.

**Returns** returns the iterator instance.

***PColorGroupIterator* GetColorGroups()**

creates a ColorGroupIterator instance with all ColorGroup resources.

**Returns** returns the iterator instance.

***PTexture2DGroupIterator* GetTexture2DGroups()**

creates a Texture2DGroupIterator instance with all base material resources.

**Returns** returns the iterator instance.

***PCompositeMaterialsIterator* GetCompositeMaterials()**

creates a CompositeMaterialsIterator instance with all CompositeMaterials resources.

**Returns** returns the iterator instance.

***PMultiPropertyGroupIterator* GetMultiPropertyGroups()**

creates a MultiPropertyGroupsIterator instance with all MultiPropertyGroup resources.

**Returns** returns the iterator instance.

***PSliceStackIterator* GetSliceStacks()**

creates a resource iterator instance with all slice stack resources.

**Returns** returns the iterator instance.

***PModel* MergeToModel()**

Merges all components and objects which are referenced by a build item into a mesh. The memory is duplicated and a new model is created.

**Returns** returns the merged model instance

***PMeshObject* AddMeshObject()**

adds an empty mesh object to the model.

**Returns** returns the mesh object instance

***PComponentsObject* AddComponentsObject()**

adds an empty component object to the model.

**Returns** returns the components object instance

***PSliceStack* AddSliceStack(const *Lib3MF\_double* dZBottom)**

creates a new model slicestack by its id

**Parameters** **dZBottom** – Bottom Z value of the slicestack

**Returns** returns the new slicestack instance

***PTexture2D* AddTexture2DFromAttachment(*CAttachment* \*pTextureAttachment)**

adds a texture2d resource to the model. Its path is given by that of an existing attachment.

**Parameters** **pTextureAttachment** – attachment containing the image data.

**Returns** returns the new texture instance.

***PBaseMaterialGroup* AddBaseMaterialGroup()**

adds an empty BaseMaterialGroup resource to the model.

**Returns** returns the new base material instance.

***PColorGroup* AddColorGroup()**

adds an empty ColorGroup resource to the model.

**Returns** returns the new ColorGroup instance.

***PTexture2DGroup* AddTexture2DGroup(*CTexture2D* \*pTexture2DInstance)**

adds an empty Texture2DGroup resource to the model.



**Parameters** **pTexture2DInstance** – The texture2D instance of the created Texture2DGroup.

**Returns** returns the new Texture2DGroup instance.

*PCompositeMaterials* **AddCompositeMaterials**(*CBaseMaterialGroup* \*pBaseMaterialGroupInstance)  
adds an empty CompositeMaterials resource to the model.

**Parameters** **pBaseMaterialGroupInstance** – The BaseMaterialGroup instance of the created CompositeMaterials.

**Returns** returns the new CompositeMaterials instance.

*PMultiPropertyGroup* **AddMultiPropertyGroup**()  
adds an empty MultiPropertyGroup resource to the model.

**Returns** returns the new MultiPropertyGroup instance.

*PBuildItem* **AddBuildItem**(*CObject* \*pObject, const *sTransform* &Transform)  
adds a build item to the model.

**Parameters**

- **pObject** – Object instance.
- **Transform** – Transformation matrix.

**Returns** returns the build item instance.

void **RemoveBuildItem**(*CBuildItem* \*pBuildItemInstance)  
removes a build item from the model

**Parameters** **pBuildItemInstance** – Build item to remove.

*PMetaDataGroup* **GetMetaDataGroup**()  
Returns the metadata of the model as MetaDataGroup

**Returns** returns an Instance of the metadatagroup of the model

*PAttachment* **AddAttachment**(const std::string &sURI, const std::string &sRelationshipType)  
adds an attachment stream to the model. The OPC part will be related to the model stream with a certain relationship type.

**Parameters**

- **sURI** – Path of the attachment
- **sRelationshipType** – Relationship type of the attachment

**Returns** Instance of the attachment object

void **RemoveAttachment**(*CAttachment* \*pAttachmentInstance)  
Removes attachment from the model.

**Parameters** **pAttachmentInstance** – Attachment instance to remove

*PAttachment* **GetAttachment**(const *Lib3MF\_uint32* nIndex)  
retrieves an attachment stream object from the model..

**Parameters** **nIndex** – Index of the attachment stream

**Returns** Instance of the attachment object

*PAttachment* **FindAttachment**(const std::string &sURI)  
retrieves an attachment stream object from the model.

**Parameters** **sURI** – Path URI in the package

**Returns** Instance of the attachment object

***Lib3MF\_uint32* GetAttachmentCount()**

retrieves the number of attachments of the model.

**Returns** Returns the number of attachments.

**bool HasPackageThumbnailAttachment()**

Retrieve whether the OPC package contains a package thumbnail.

**Returns** returns whether the OPC package contains a package thumbnail

***PAttachment* CreatePackageThumbnailAttachment()**

Create a new or the existing package thumbnail for the OPC package.

**Returns** Instance of a new or the existing thumbnailattachment object.

***PAttachment* GetPackageThumbnailAttachment()**

Get the attachment to the OPC package containing the package thumbnail.

**Returns** Instance of the thumbnailattachment object or NULL.

**void RemovePackageThumbnailAttachment()**

Remove the attachment to the OPC package containing the package thumbnail.

**void AddCustomContentType(const std::string &sExtension, const std::string &sContentType)**

Adds a new Content Type to the model.

**Parameters**

- **sExtension** – File Extension
- **sContentType** – Content Type Identifier

**void RemoveCustomContentType(const std::string &sExtension)**

Removes a custom Content Type from the model (UTF8 version).

**Parameters** **sExtension** – File Extension

**void SetRandomNumberCallback(const *RandomNumberCallback* pTheCallback, const *Lib3MF\_pvoid* pUserData)**

Sets the random number generator callback for use in the library

**Parameters**

- **pTheCallback** – The callback used to generate random numbers
- **pUserData** – Userdata to be passed to the callback function

***PKeyStore* GetKeyStore()**

Gets the keystore associated with this model

**Returns** The package keystore

**typedef std::shared\_ptr<*CModel*> Lib3MF::PModel**

Shared pointer to CModel to easily allow reference counting.

## CMultiPropertyGroup

class Lib3MF::CMultiPropertyGroup : public CResource

*Lib3MF\_uint32* **GetCount**()

Retrieves the count of MultiProperty-s in the MultiPropertyGroup.

**Returns** returns the count of MultiProperty-s

void **GetAllPropertyIDs**(std::vector<*Lib3MF\_uint32*> &PropertyIDsBuffer)

returns all the PropertyIDs of all MultiProperty-s in this MultiPropertyGroup

**Parameters** **PropertyIDsBuffer** – PropertyID of the MultiProperty-s in the MultiProperty-Group.

*Lib3MF\_uint32* **AddMultiProperty**(const *CInputVector*<*Lib3MF\_uint32*> &PropertyIDsBuffer)

Adds a new MultiProperty to the MultiPropertyGroup.

**Parameters** **PropertyIDsBuffer** – The PropertyIDs of the new MultiProperty.

**Returns** returns the PropertyID of the new MultiProperty in the MultiPropertyGroup.

void **SetMultiProperty**(const *Lib3MF\_uint32* nPropertyID, const *CInputVector*<*Lib3MF\_uint32*> &PropertyIDsBuffer)

Sets the PropertyIDs of a MultiProperty.

**Parameters**

- **nPropertyID** – the PropertyID of the MultiProperty to be changed.
- **PropertyIDsBuffer** – The new PropertyIDs of the MultiProperty

void **GetMultiProperty**(const *Lib3MF\_uint32* nPropertyID, std::vector<*Lib3MF\_uint32*> &PropertyIDsBuffer)

Obtains the PropertyIDs of a MultiProperty.

**Parameters**

- **nPropertyID** – the PropertyID of the MultiProperty to be queried.
- **PropertyIDsBuffer** – The PropertyIDs of the MultiProperty

void **RemoveMultiProperty**(const *Lib3MF\_uint32* nPropertyID)

Removes a MultiProperty from this MultiPropertyGroup.

**Parameters** **nPropertyID** – the PropertyID of the MultiProperty to be removed.

*Lib3MF\_uint32* **GetLayerCount**()

Retrieves the number of layers of this MultiPropertyGroup.

**Returns** returns the number of layers

*Lib3MF\_uint32* **AddLayer**(const *sMultiPropertyLayer* &TheLayer)

Adds a MultiPropertyLayer to this MultiPropertyGroup.

**Parameters** **TheLayer** – The MultiPropertyLayer to add to this MultiPropertyGroup

**Returns** returns the index of this MultiPropertyLayer

*sMultiPropertyLayer* **GetLayer**(const *Lib3MF\_uint32* nLayerIndex)

Obtains a MultiPropertyLayer of this MultiPropertyGroup.

**Parameters** **nLayerIndex** – The Index of the MultiPropertyLayer queried

**Returns** The MultiPropertyLayer with index LayerIndex within MultiPropertyGroup

void **RemoveLayer**(const *Lib3MF\_uint32* nLayerIndex)  
Removes a MultiPropertyLayer from this MultiPropertyGroup.

**Parameters** **nLayerIndex** – The Index of the MultiPropertyLayer to be removed

typedef std::shared\_ptr<*CMultiPropertyGroup*> Lib3MF::P**MultiPropertyGroup**  
Shared pointer to CMultiPropertyGroup to easily allow reference counting.

## CMultiPropertyGroupIterator

class Lib3MF::C**MultiPropertyGroupIterator** : public *CResourceIterator*

*PMultiPropertyGroup* **GetCurrentMultiPropertyGroup**()  
Returns the MultiPropertyGroup the iterator points at.

**Returns** returns the MultiPropertyGroup instance.

typedef std::shared\_ptr<*CMultiPropertyGroupIterator*> Lib3MF::P**MultiPropertyGroupIterator**  
Shared pointer to CMultiPropertyGroupIterator to easily allow reference counting.

## CObject

class Lib3MF::C**Object** : public *CResource*

*eObjectType* **GetType**()  
Retrieves an object's type

**Returns** returns object type enum.

void **SetType**(const *eObjectType* eObjectType)  
Sets an object's type

**Parameters** **eObjectType** – object type enum.

std::string **GetName**()  
Retrieves an object's name

**Returns** returns object name.

void **SetName**(const std::string &sName)  
Sets an object's name string

**Parameters** **sName** – new object name.

std::string **GetPartNumber**()  
Retrieves an object's part number

**Returns** returns object part number.

void **SetPartNumber**(const std::string &sPartNumber)  
Sets an objects partnumber string

**Parameters** **sPartNumber** – new object part number.

bool **IsMeshObject**()  
Retrieves, if an object is a mesh object

**Returns** returns, whether the object is a mesh object

bool **IsComponentsObject**()  
Retrieves, if an object is a components object

**Returns** returns, whether the object is a components object

bool **IsValid()**

Retrieves, if the object is valid according to the core spec. For mesh objects, we distinguish between the type attribute of the object: In case of object type other, this always means false. In case of object type model or solidsupport, this means, if the mesh suffices all requirements of the core spec chapter 4.1. In case of object type support or surface, this always means true. A component object is valid if and only if it contains at least one component and all child components are valid objects.

**Returns** returns whether the object is a valid object description

void **SetAttachmentAsThumbnail**(*CAttachment* \*pAttachment)

Use an existing attachment as thumbnail for this object

**Parameters** **pAttachment** – Instance of a new or the existing thumbnailattachment object.

*CAttachment* **GetThumbnailAttachment()**

Get the attachment containing the object thumbnail.

**Returns** Instance of the thumbnailattachment object or NULL.

void **ClearThumbnailAttachment()**

Clears the attachment. The attachment instance is not removed from the package.

*sBox* **GetOutbox()**

Returns the outbox of a build item

**Returns** Outbox of this build item

std::string **GetUUID**(bool &bHasUUID)

Retrieves an object's uuid string (see production extension specification)

**Parameters** **bHasUUID** – flag whether the build item has a UUID

**Returns** returns object uuid.

void **SetUUID**(const std::string &sUUID)

Sets a build object's uuid string (see production extension specification)

**Parameters** **sUUID** – new object uuid string.

*PMetaDataGroup* **GetMetaDataGroup()**

Returns the metadatagroup of this object

**Returns** returns an Instance of the metadatagroup of this object

void **SetSlicesMeshResolution**(const *eSlicesMeshResolution* eMeshResolution)

set the meshresolution of the mesh object

**Parameters** **eMeshResolution** – meshresolution of this object

*eSlicesMeshResolution* **GetSlicesMeshResolution()**

get the meshresolution of the mesh object

**Returns** meshresolution of this object

bool **HasSlices**(const bool bRecursive)

returns whether the Object has a slice stack. If Recursive is true, also checks whether any references object has a slice stack

**Parameters** **bRecursive** – check also all referenced objects?

**Returns** does the object have a slice stack?

void **ClearSliceStack()**

unlinks the attached slicestack from this object. If no slice stack is attached, do nothing.

***PSliceStack* GetSliceStack()**

get the Slicestack attached to the object

**Returns** returns the slicestack instance

void **AssignSliceStack**(*CSliceStack* \*pSliceStackInstance)

assigns a slicestack to the object

**Parameters** **pSliceStackInstance** – the new slice stack of this Object

typedef std::shared\_ptr<*CObject*> Lib3MF::PObject

Shared pointer to CObject to easily allow reference counting.

**CObjectIterator**

class Lib3MF::CObjectIterator : public *CResourceIterator*

***PObject* GetCurrentObject()**

Returns the Object the iterator points at.

**Returns** returns the Object instance.

typedef std::shared\_ptr<*CObjectIterator*> Lib3MF::PObjectIterator

Shared pointer to CObjectIterator to easily allow reference counting.

**CPackagePart**

class Lib3MF::CPackagePart : public *CBase*

**std::string GetPath()**

Returns the absolute path of this PackagePart.

**Returns** Returns the absolute path of this PackagePart

void **SetPath**(const std::string &sPath)

Sets the absolute path of this PackagePart.

**Parameters** **sPath** – Sets the absolute path of this PackagePart.

typedef std::shared\_ptr<*CPackagePart*> Lib3MF::PPackagePart

Shared pointer to CPackagePart to easily allow reference counting.

**CReader**

class Lib3MF::CReader : public *CBase*

void **ReadFromFile**(const std::string &sFilename)

Reads a model from a file. The file type is specified by the Model Reader class

**Parameters** **sFilename** – Filename to read from

void **ReadFromBuffer**(const *CInputVector*<*Lib3MF\_uint8*> &BufferBuffer)

Reads a model from a memory buffer.

**Parameters** **BufferBuffer** – Buffer to read from

void **ReadFromCallback**(const *ReadCallback* pTheReadCallback, const *Lib3MF\_uint64* nStreamSize, const *SeekCallback* pTheSeekCallback, const *Lib3MF\_pvoid* pUserData)

Reads a model and from the data provided by a callback function

**Parameters**

- **pTheReadCallback** – Callback to call for reading a data chunk
- **nStreamSize** – number of bytes the callback returns
- **pTheSeekCallback** – Callback to call for seeking in the stream.
- **pUserData** – Userdata that is passed to the callback function

void **SetProgressCallback**(const *ProgressCallback* pProgressCallback, const *Lib3MF\_pvoid* pUserData)

Set the progress callback for calls to this writer

**Parameters**

- **pProgressCallback** – pointer to the callback function.
- **pUserData** – pointer to arbitrary user data that is passed without modification to the callback.

void **AddRelationToRead**(const std::string &sRelationshipType)

Adds a relationship type which shall be read as attachment in memory while loading

**Parameters** **sRelationshipType** – String of the relationship type

void **RemoveRelationToRead**(const std::string &sRelationshipType)

Removes a relationship type which shall be read as attachment in memory while loading

**Parameters** **sRelationshipType** – String of the relationship type

void **SetStrictModeActive**(const bool bStrictModeActive)

Activates (deactivates) the strict mode of the reader.

**Parameters** **bStrictModeActive** – flag whether strict mode is active or not.

bool **GetStrictModeActive**()

Queries whether the strict mode of the reader is active or not

**Returns** returns flag whether strict mode is active or not.

std::string **GetWarning**(const *Lib3MF\_uint32* nIndex, *Lib3MF\_uint32* &nErrorCode)

Returns Warning and Error Information of the read process

**Parameters**

- **nIndex** – Index of the Warning. Valid values are 0 to WarningCount - 1
- **nErrorCode** – filled with the error code of the warning

**Returns** the message of the warning

*Lib3MF\_uint32* **GetWarningCount**()

Returns Warning and Error Count of the read process

**Returns** filled with the count of the occurred warnings.

void **AddKeyWrappingCallback**(const std::string &sConsumerID, const *KeyWrappingCallback* pTheCallback, const *Lib3MF\_pvoid* pUserData)

Registers a callback to deal with key wrapping mechanism from keystore

**Parameters**

- **sConsumerID** – The ConsumerID to register for

- **pTheCallback** – The callback used to decrypt data key
- **pUserData** – Userdata that is passed to the callback function

void **SetContentEncryptionCallback**(const *ContentEncryptionCallback* pTheCallback, const *Lib3MF\_pvoid* pUserData)

Registers a callback to deal with encryption of content

#### Parameters

- **pTheCallback** – The callback used to encrypt content
- **pUserData** – Userdata that is passed to the callback function

typedef std::shared\_ptr<*CReader*> Lib3MF::PReader

Shared pointer to CReader to easily allow reference counting.

## CResource

class Lib3MF::CResource : public *CBase*

*Lib3MF\_uint32* **GetResourceID()**

Retrieves the unique id of this resource within a package. This function will be removed in a later release in favor of GetUniqueResourceID

**Returns** Retrieves the unique id of this resource within a package.

*Lib3MF\_uint32* **GetUniqueResourceID()**

Retrieves the unique id of this resource within a package.

**Returns** Retrieves the unique id of this resource within a package.

*PPackagePart* **PackagePart()**

Returns the PackagePart within which this resource resides

**Returns** the PackagePart within which this resource resides.

void **SetPackagePart**(*CPackagePart* \*pPackagePart)

Sets the new PackagePart within which this resource resides

**Parameters** **pPackagePart** – the new PackagePart within which this resource resides.

*Lib3MF\_uint32* **GetModelResourceID()**

Retrieves the id of this resource within a model.

**Returns** Retrieves the id of this resource within a model.

typedef std::shared\_ptr<*CResource*> Lib3MF::PResource

Shared pointer to CResource to easily allow reference counting.

## CResourceData

class Lib3MF::CResourceData : public *CBase*

*PPackagePart* **GetPath()**

Gets the encrypted part path

**Returns** The part path

eEncryptionAlgorithm **GetEncryptionAlgorithm()**

Gets the encryption algorithm used to encrypt this ResourceData



**Returns** The encryption algorithm

eCompression **GetCompression()**

Tells whether this ResourceData is compressed or not

**Returns** The compression method

void **GetAdditionalAuthenticationData**(std::vector<Lib3MF\_uint8> &ByteDataBuffer)

Tells whether this ResourceData is compressed or not

**Parameters** **ByteDataBuffer** – The compression method

typedef std::shared\_ptr<CResourceData> Lib3MF::PResourceData

Shared pointer to CResourceData to easily allow reference counting.

## CResourceDataGroup

class Lib3MF::CResourceDataGroup : public CBase

std::string **GetKeyUUID()**

Sets the resourcedatagroup keyuuid

**Returns** The new resourcedatagroup keyuuid.

*PAccessRight* **AddAccessRight**(CConsumer \*pConsumer, const *eWrappingAlgorithm* eWrappingAlgorithm, const *eMgfAlgorithm* eMgfAlgorithm, const *eDigestMethod* eDigestMethod)

Add accessright to resourcedatagroup element

**Parameters**

- **pConsumer** – The Consumer reference
- **eWrappingAlgorithm** – The key wrapping algorithm to be used
- **eMgfAlgorithm** – The mask generation function to be used
- **eDigestMethod** – The digest mechanism to be used

**Returns** The access right instance

*PAccessRight* **FindAccessRightByConsumer**(CConsumer \*pConsumer)

Finds the AccessRight associated with a Consumer

**Parameters** **pConsumer** – The Consumer instance

**Returns** The AccessRight instance

void **RemoveAccessRight**(CConsumer \*pConsumer)

Removes access from a Consumer on this resource data group

**Parameters** **pConsumer** – The Consumer instance

typedef std::shared\_ptr<CResourceDataGroup> Lib3MF::PResourceDataGroup

Shared pointer to CResourceDataGroup to easily allow reference counting.

## CResourceIterator

class Lib3MF::CResourceIterator : public CBase

bool **MoveNext**()

Iterates to the next resource in the list.

**Returns** Iterates to the next resource in the list.

bool **MovePrevious**()

Iterates to the previous resource in the list.

**Returns** Iterates to the previous resource in the list.

*PResource* **GetCurrent**()

Returns the resource the iterator points at.

**Returns** returns the resource instance.

*PResourceIterator* **Clone**()

Creates a new resource iterator with the same resource list.

**Returns** returns the cloned Iterator instance

*Lib3MF\_uint64* **Count**()

Returns the number of resouces the iterator captures.

**Returns** returns the number of resouces the iterator captures.

typedef std::shared\_ptr<*CResourceIterator*> Lib3MF::PResourceIterator

Shared pointer to CResourceIterator to easily allow reference counting.

## CSlice

class Lib3MF::CSlice : public CBase

void **SetVertices**(const *CInputVector*<*sPosition2D*> &VerticesBuffer)

Set all vertices of a slice. All polygons will be cleared.

**Parameters** **VerticesBuffer** – contains the positions.

void **GetVertices**(std::vector<*sPosition2D*> &VerticesBuffer)

Get all vertices of a slice

**Parameters** **VerticesBuffer** – contains the positions.

*Lib3MF\_uint64* **GetVertexCount**()

Get the number of vertices in a slice

**Returns** the number of vertices in the slice

*Lib3MF\_uint64* **AddPolygon**(const *CInputVector*<*Lib3MF\_uint32*> &IndicesBuffer)

Add a new polygon to this slice

**Parameters** **IndicesBuffer** – the new indices of the new polygon

**Returns** the index of the new polygon

*Lib3MF\_uint64* **GetPolygonCount**()

Get the number of polygons in the slice

**Returns** the number of polygons in the slice

void **SetPolygonIndices**(const *Lib3MF\_uint64* nIndex, const *CInputVector*<*Lib3MF\_uint32*> &IndicesBuffer)

Set all indices of a polygon

**Parameters**

- **nIndex** – the index of the polygon to manipulate
- **IndicesBuffer** – the new indices of the index-th polygon

void **GetPolygonIndices**(const *Lib3MF\_uint64* nIndex, std::vector<*Lib3MF\_uint32*> &IndicesBuffer)

Get all vertices of a slice

**Parameters**

- **nIndex** – the index of the polygon to manipulate
- **IndicesBuffer** – the indices of the index-th polygon

*Lib3MF\_uint64* **GetPolygonIndexCount**(const *Lib3MF\_uint64* nIndex)

Get the number of vertices in a slice

**Parameters** **nIndex** – the index of the polygon to manipulate

**Returns** the number of indices of the index-th polygon

*Lib3MF\_double* **GetZTop**()

Get the upper Z-Coordinate of this slice.

**Returns** the upper Z-Coordinate of this slice

typedef std::shared\_ptr<*CSlice*> **Lib3MF::PSlice**

Shared pointer to CSlice to easily allow reference counting.

## CSliceStack

class **Lib3MF::CSliceStack** : public *CResource*

*Lib3MF\_double* **GetBottomZ**()

Get the lower Z-Coordinate of the slice stack.

**Returns** the lower Z-Coordinate the slice stack

*Lib3MF\_uint64* **GetSliceCount**()

Returns the number of slices

**Returns** the number of slices

*PSlice* **GetSlice**(const *Lib3MF\_uint64* nSliceIndex)

Query a slice from the slice stack

**Parameters** **nSliceIndex** – the index of the slice

**Returns** the Slice instance

*PSlice* **AddSlice**(const *Lib3MF\_double* dZTop)

Returns the number of slices

**Parameters** **dZTop** – upper Z coordinate of the slice

**Returns** a new Slice instance

*Lib3MF\_uint64* **GetSliceRefCount**()

Returns the number of slice refs

**Returns** the number of slicereferences

void **AddSliceStackReference**(*CSliceStack* \*pTheSliceStack)  
Adds another existing slicestack as sliceref in this slicestack

**Parameters** **pTheSliceStack** – the slicestack to use as sliceref

*PSliceStack* **GetSliceStackReference**(const *Lib3MF\_uint64* nSliceRefIndex)  
Adds another existing slicestack as sliceref in this slicestack

**Parameters** **nSliceRefIndex** – the index of the slice ref

**Returns** the slicestack that is used as sliceref

void **CollapseSliceReferences**()  
Removes the indirection of slices via slice-refs, i.e. creates the slices of all slice refs of this SliceStack as actual slices of this SliceStack. All previously existing slices or slicerefs will be removed.

void **SetOwnPath**(const std::string &sPath)  
Sets the package path where this Slice should be stored. Input an empty string to reset the path

**Parameters** **sPath** – the package path where this Slice should be stored

std::string **GetOwnPath**()  
Obtains the package path where this Slice should be stored. Returns an empty string if the slicestack is stored within the root model.

**Returns** the package path where this Slice will be stored

typedef std::shared\_ptr<*CSliceStack*> **Lib3MF::PSliceStack**  
Shared pointer to CSliceStack to easily allow reference counting.

## CSliceStackIterator

class **Lib3MF::CSliceStackIterator** : public *CResourceIterator*

*PSliceStack* **GetCurrentSliceStack**()  
Returns the SliceStack the iterator points at.

**Returns** returns the SliceStack instance.

typedef std::shared\_ptr<*CSliceStackIterator*> **Lib3MF::PSliceStackIterator**  
Shared pointer to CSliceStackIterator to easily allow reference counting.

## CTexture2D

class **Lib3MF::CTexture2D** : public *CResource*

*PAttachment* **GetAttachment**()  
Retrieves the attachment located at the path of the texture.

**Returns** attachment that holds the texture's image information.

void **SetAttachment**(*CAttachment* \*pAttachment)  
Sets the texture's package path to the path of the attachment.

**Parameters** **pAttachment** – attachment that holds the texture's image information.

*eTextureType* **GetContentType**()  
Retrieves a texture's content type.

**Returns** returns content type enum.

void **SetContentType**(const *eTextureType* eContentType)  
Retrieves a texture's content type.

**Parameters** **eContentType** – new Content Type

void **GetTileStyleUV**(*eTextureTileStyle* &eTileStyleU, *eTextureTileStyle* &eTileStyleV)  
Retrieves a texture's tilestyle type.

**Parameters**

- **eTileStyleU** – returns tilestyle type enum.
- **eTileStyleV** – returns tilestyle type enum.

void **SetTileStyleUV**(const *eTextureTileStyle* eTileStyleU, const *eTextureTileStyle* eTileStyleV)  
Sets a texture's tilestyle type.

**Parameters**

- **eTileStyleU** – new tilestyle type enum.
- **eTileStyleV** – new tilestyle type enum.

*eTextureFilter* **GetFilter**()  
Retrieves a texture's filter type.

**Returns** returns filter type enum.

void **SetFilter**(const *eTextureFilter* eFilter)  
Sets a texture's filter type.

**Parameters** **eFilter** – sets new filter type enum.

typedef std::shared\_ptr<*CTexture2D*> Lib3MF::PTexture2D  
Shared pointer to CTexture2D to easily allow reference counting.

## CTexture2DGroup

class Lib3MF::CTexture2DGroup : public *CResource*

*Lib3MF\_uint32* **GetCount**()  
Retrieves the count of tex2coords in the Texture2DGroup.

**Returns** returns the count of tex2coords.

void **GetPropertyIDs**(std::vector<*Lib3MF\_uint32*> &PropertyIDsBuffer)  
returns all the PropertyIDs of all tex2coords in this Texture2DGroup

**Parameters** **PropertyIDsBuffer** – PropertyID of the tex2coords in the Texture2DGroup.

*Lib3MF\_uint32* **AddTex2Coord**(const *sTex2Coord* &UVCoordinate)  
Adds a new tex2coord to the Texture2DGroup

**Parameters** **UVCoordinate** – The u/v-coordinate within the texture, horizontally right/vertically up from the origin in the lower left of the texture.

**Returns** returns new PropertyID of the new tex2coord in the Texture2DGroup.

*sTex2Coord* **GetTex2Coord**(const *Lib3MF\_uint32* nPropertyID)  
Obtains a tex2coord to the Texture2DGroup

**Parameters** **nPropertyID** – the PropertyID of the tex2coord in the Texture2DGroup.

**Returns** The u/v-coordinate within the texture, horizontally right/vertically up from the origin in the lower left of the texture.

void **RemoveTex2Coord**(const *Lib3MF\_uint32* nPropertyID)

Removes a tex2coords from the Texture2DGroup.

**Parameters** **nPropertyID** – PropertyID of the tex2coords in the Texture2DGroup.

*PTexture2D* **GetTexture2D**()

Obtains the texture2D instance of this group.

**Returns** the texture2D instance of this group.

typedef std::shared\_ptr<*CTexture2DGroup*> **Lib3MF::PTexture2DGroup**

Shared pointer to CTexture2DGroup to easily allow reference counting.

### CTexture2DGroupIterator

class **Lib3MF::CTexture2DGroupIterator** : public *CResourceIterator*

*PTexture2DGroup* **GetCurrentTexture2DGroup**()

Returns the Texture2DGroup the iterator points at.

**Returns** returns the Texture2DGroup instance.

typedef std::shared\_ptr<*CTexture2DGroupIterator*> **Lib3MF::PTexture2DGroupIterator**

Shared pointer to CTexture2DGroupIterator to easily allow reference counting.

### CTexture2DIterator

class **Lib3MF::CTexture2DIterator** : public *CResourceIterator*

*PTexture2D* **GetCurrentTexture2D**()

Returns the Texture2D the iterator points at.

**Returns** returns the Texture2D instance.

typedef std::shared\_ptr<*CTexture2DIterator*> **Lib3MF::PTexture2DIterator**

Shared pointer to CTexture2DIterator to easily allow reference counting.

### CWriter

class **Lib3MF::CWriter** : public *CBase*

void **WriteToFile**(const std::string &sFilename)

Writes out the model as file. The file type is specified by the Model Writer class.

**Parameters** **sFilename** – Filename to write into

*Lib3MF\_uint64* **GetStreamSize**()

Retrieves the size of the full 3MF file stream.

**Returns** the stream size

void **WriteToBuffer**(std::vector<*Lib3MF\_uint8*> &BufferBuffer)

Writes out the 3MF file into a memory buffer

**Parameters** **BufferBuffer** – buffer to write into

void **WriteToCallback**(const *WriteCallback* pTheWriteCallback, const *SeekCallback* pTheSeekCallback, const *Lib3MF\_pvoid* pUserData)

Writes out the model and passes the data to a provided callback function. The file type is specified by the Model Writer class.

**Parameters**

- **pTheWriteCallback** – Callback to call for writing a data chunk
- **pTheSeekCallback** – Callback to call for seeking in the stream
- **pUserData** – Userdata that is passed to the callback function

void **SetProgressCallback**(const *ProgressCallback* pProgressCallback, const *Lib3MF\_pvoid* pUserData)

Set the progress callback for calls to this writer

**Parameters**

- **pProgressCallback** – pointer to the callback function.
- **pUserData** – pointer to arbitrary user data that is passed without modification to the callback.

*Lib3MF\_uint32* **GetDecimalPrecision**()

Returns the number of digits after the decimal point to be written in each vertex coordinate-value.

**Returns** The number of digits to be written in each vertex coordinate-value after the decimal point.

void **SetDecimalPrecision**(const *Lib3MF\_uint32* nDecimalPrecision)

Sets the number of digits after the decimal point to be written in each vertex coordinate-value.

**Parameters** **nDecimalPrecision** – The number of digits to be written in each vertex coordinate-value after the decimal point.

void **SetStrictModeActive**(const bool bStrictModeActive)

Activates (deactivates) the strict mode of the reader.

**Parameters** **bStrictModeActive** – flag whether strict mode is active or not.

bool **GetStrictModeActive**()

Queries whether the strict mode of the reader is active or not

**Returns** returns flag whether strict mode is active or not.

std::string **GetWarning**(const *Lib3MF\_uint32* nIndex, *Lib3MF\_uint32* &nErrorCode)

Returns Warning and Error Information of the read process

**Parameters**

- **nIndex** – Index of the Warning. Valid values are 0 to WarningCount - 1
- **nErrorCode** – filled with the error code of the warning

**Returns** the message of the warning

*Lib3MF\_uint32* **GetWarningCount**()

Returns Warning and Error Count of the read process

**Returns** filled with the count of the occurred warnings.

void **AddKeyWrappingCallback**(const std::string &sConsumerID, const *KeyWrappingCallback* pTheCallback, const *Lib3MF\_pvoid* pUserData)

Registers a callback to deal with data key encryption/decryption from keystore

**Parameters**

- **sConsumerID** – The ConsumerID to register for
- **pTheCallback** – The callback to be called for wrapping and encryption key
- **pUserData** – Userdata that is passed to the callback function

void **SetContentEncryptionCallback**(const *ContentEncryptionCallback* pTheCallback, const *Lib3MF\_pvoid* pUserData)

Registers a callback to deal with encryption of content

**Parameters**

- **pTheCallback** – The callback used to encrypt content
- **pUserData** – Userdata that is passed to the callback function

typedef std::shared\_ptr<*CWriter*> **Lib3MF::PWriter**

Shared pointer to CWriter to easily allow reference counting.

## 1.2 C-language bindings

This space describes the usage of lib3mf in a C host application.

TODO

## 1.3 Python-language bindings

TODO

## 1.4 Pascal-language bindings

TODO

## 1.5 C#-language bindings

This space describes the usage of lib3mf in a C# host application.

TODO

## 1.6 Golang-language bindings

TODO



## 1.7 NodeJS-language bindings

TODO



## OBTAINING LIB3MF

Simply download the precompiled binary SDK <https://github.com/3MFConsortium/lib3mf/releases>.



## USING LIB3MF

Although the different language bindings are kept as similar as possible, the usage of lib3mf still depends your programming language. You are best-off starting with one of the examples distributed in the SDK (<https://github.com/3MFConsortium/lib3mf/releases>).

In addition, the home pages for each language binding give detailed instructions on how to use them.



## META INFORMATION

[source/license](#)

[Reporting Bugs](#)

[The 3MF Consortium](#)

[Specification of the 3MF format](#)





## INDICES AND TABLES

- `genindex`
- `search`



## INDEX

### C

ContentEncryptionCallback (C++ type), 15

### E

eBeamLatticeBallMode (C++ enum), 10

eBeamLatticeBallMode::All (C++ enumerator), 10

eBeamLatticeBallMode::eBlendMethod (C++ enum), 11

eBeamLatticeBallMode::eBlendMethod::Mix (C++ enumerator), 11

eBeamLatticeBallMode::eBlendMethod::Multiply (C++ enumerator), 11

eBeamLatticeBallMode::eBlendMethod::NoBlendMethod (C++ enumerator), 11

eBeamLatticeBallMode::eCompression (C++ enum), 12

eBeamLatticeBallMode::eCompression::Deflate (C++ enumerator), 12

eBeamLatticeBallMode::eCompression::NoCompression (C++ enumerator), 12

eBeamLatticeBallMode::eDigestMethod (C++ enum), 12

eBeamLatticeBallMode::eDigestMethod::SHA1 (C++ enumerator), 12

eBeamLatticeBallMode::eDigestMethod::SHA256 (C++ enumerator), 12

eBeamLatticeBallMode::eEncryptionAlgorithm (C++ enum), 11

eBeamLatticeBallMode::eEncryptionAlgorithm::AES256\_GCM (C++ enumerator), 11

eBeamLatticeBallMode::eMgfAlgorithm (C++ enum), 11

eBeamLatticeBallMode::eMgfAlgorithm::MGF1\_SHA1 (C++ enumerator), 11

eBeamLatticeBallMode::eMgfAlgorithm::MGF1\_SHA224 (C++ enumerator), 12

eBeamLatticeBallMode::eMgfAlgorithm::MGF1\_SHA256 (C++ enumerator), 12

eBeamLatticeBallMode::eMgfAlgorithm::MGF1\_SHA384 (C++ enumerator), 12

eBeamLatticeBallMode::eMgfAlgorithm::MGF1\_SHA512 (C++ enumerator), 12

eBeamLatticeBallMode::eProgressIdentifier (C++ enum), 10

eBeamLatticeBallMode::eProgressIdentifier::CLEANUP (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::CREATEOPCPACKAGE (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::DONE (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::EXTRACTOPCPACKAGE (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::QUERYCANCELED (C++ enumerator), 10

eBeamLatticeBallMode::eProgressIdentifier::READBUILD (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::READCUSTOMATTACHMENT (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::READMESH (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::READNONROOTMODEL (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::READRESOURCES (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::READROOTMODEL (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::READSLICES (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::READSTREAM (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::READTEXTURETACHMENT (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::WRITEATTACHMENT (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::WRITECONTENTTYPE (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::WRITEKEYSTORE (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::WRITEMODELSTORAGE (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::WRITENOBJECTS (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::WRITENODES (C++ enumerator), 11

eBeamLatticeBallMode::eProgressIdentifier::WRITEFROMMODEL:Auto (C++ enumerator), 10  
 (C++ enumerator), 11  
 eBeamLatticeBallMode::eProgressIdentifier::WRITEFROMMODEL:TextureFilter::Linear (C++ enumerator), 10  
 (C++ enumerator), 11  
 eBeamLatticeBallMode::eProgressIdentifier::WRITEFROMMODEL:TextureFilter::Nearest (C++ enumerator), 10  
 (C++ enumerator), 11  
 eBeamLatticeBallMode::eProgressIdentifier::WRITEFROMMODEL:TextureTileStyle::Clamp (C++ enumerator), 10  
 (C++ enumerator), 11  
 eBeamLatticeBallMode::eProgressIdentifier::WRITEFROMMODEL:TextureTileStyle::Mirror (C++ enumerator), 10  
 (C++ enumerator), 11  
 eBeamLatticeBallMode::eProgressIdentifier::WRITEFROMMODEL:TextureTileStyle::NoTileStyle (C++ enumerator), 10  
 (C++ enumerator), 11  
 eBeamLatticeBallMode::eWrappingAlgorithm eTextureTileStyle::Wrap (C++ enumerator), 10  
 (C++ enum), 11 eTextureType (C++ enum), 10  
 eBeamLatticeBallMode::eWrappingAlgorithm::RSA\_OAEP eTextureType::JPEG (C++ enumerator), 10  
 (C++ enumerator), 11 eTextureType::PNG (C++ enumerator), 10  
 eBeamLatticeBallMode::Mixed (C++ enumerator), eTextureType::Unknown (C++ enumerator), 10  
 10  
 eBeamLatticeBallMode::None (C++ enumerator), 10  
 eBeamLatticeCapMode (C++ enum), 10  
 eBeamLatticeCapMode::Butt (C++ enumerator), 10  
 eBeamLatticeCapMode::HemiSphere (C++ enumerator), 10  
 eBeamLatticeCapMode::Sphere (C++ enumerator), 10  
 eBeamLatticeClipMode (C++ enum), 10  
 eBeamLatticeClipMode::Inside (C++ enumerator), 10  
 eBeamLatticeClipMode::NoClipMode (C++ enumerator), 10  
 eBeamLatticeClipMode::Outside (C++ enumerator), 10  
 eModelUnit (C++ enum), 9  
 eModelUnit::CentiMeter (C++ enumerator), 9  
 eModelUnit::Foot (C++ enumerator), 9  
 eModelUnit::Inch (C++ enumerator), 9  
 eModelUnit::Meter (C++ enumerator), 9  
 eModelUnit::MicroMeter (C++ enumerator), 9  
 eModelUnit::MilliMeter (C++ enumerator), 9  
 eObjectType (C++ enum), 9  
 eObjectType::Model (C++ enumerator), 10  
 eObjectType::Other (C++ enumerator), 10  
 eObjectType::SolidSupport (C++ enumerator), 10  
 eObjectType::Support (C++ enumerator), 10  
 ePropertyType (C++ enum), 9  
 ePropertyType::BaseMaterial (C++ enumerator), 9  
 ePropertyType::Colors (C++ enumerator), 9  
 ePropertyType::Composite (C++ enumerator), 9  
 ePropertyType::Multi (C++ enumerator), 9  
 ePropertyType::NoPropertyType (C++ enumerator), 9  
 ePropertyType::TexCoord (C++ enumerator), 9  
 eSlicesMeshResolution (C++ enum), 9  
 eSlicesMeshResolution::Fullres (C++ enumerator), 9  
 eSlicesMeshResolution::Lowres (C++ enumerator), 9  
 eTextureFilter (C++ enum), 10

**K**  
 KeyWrappingCallback (C++ type), 14

**L**  
 Lib3MF::AccessRight (C++ class), 16  
 Lib3MF::AccessRight::GetConsumer (C++ function), 16  
 Lib3MF::AccessRight::GetDigestMethod (C++ function), 16  
 Lib3MF::AccessRight::GetMgfAlgorithm (C++ function), 16  
 Lib3MF::AccessRight::GetWrappingAlgorithm (C++ function), 16  
 Lib3MF::Attachment (C++ class), 16  
 Lib3MF::Attachment::GetPath (C++ function), 16  
 Lib3MF::Attachment::GetRelationshipType (C++ function), 17  
 Lib3MF::Attachment::GetStreamSize (C++ function), 17  
 Lib3MF::Attachment::PackagePart (C++ function), 17  
 Lib3MF::Attachment::ReadFromBuffer (C++ function), 17  
 Lib3MF::Attachment::ReadFromFile (C++ function), 17  
 Lib3MF::Attachment::SetPath (C++ function), 16  
 Lib3MF::Attachment::SetRelationshipType (C++ function), 17  
 Lib3MF::Attachment::WriteToBuffer (C++ function), 17  
 Lib3MF::Attachment::WriteToFile (C++ function), 17  
 Lib3MF::CBase (C++ class), 17  
 Lib3MF::CBaseMaterialGroup (C++ class), 17  
 Lib3MF::CBaseMaterialGroup::AddMaterial (C++ function), 18  
 Lib3MF::CBaseMaterialGroup::GetAllPropertyIDs (C++ function), 17  
 Lib3MF::CBaseMaterialGroup::GetCount (C++ function), 17

Lib3MF::CBaseMaterialGroup::GetDisplayColor (C++ function), 18	(C++ function), 21
Lib3MF::CBaseMaterialGroup::GetName (C++ function), 18	Lib3MF::CBuildItem::GetObjectTransform (C++ function), 21
Lib3MF::CBaseMaterialGroup::RemoveMaterial (C++ function), 18	Lib3MF::CBuildItem::GetOutbox (C++ function), 21
Lib3MF::CBaseMaterialGroup::SetDisplayColor (C++ function), 18	Lib3MF::CBuildItem::GetPartNumber (C++ func- tion), 21
Lib3MF::CBaseMaterialGroup::SetName (C++ function), 18	Lib3MF::CBuildItem::GetUUID (C++ function), 21
Lib3MF::CBaseMaterialGroupIterator (C++ class), 18	Lib3MF::CBuildItem::HasObjectTransform (C++ function), 21
Lib3MF::CBaseMaterialGroupIterator::GetCurrentBaseMaterialGroup (C++ function), 18	Lib3MF::CBuildItem::SetObjectTransform (C++ function), 21
Lib3MF::CBeamLattice (C++ class), 19	Lib3MF::CBuildItem::SetPartNumber (C++ func- tion), 21
Lib3MF::CBeamLattice::GetBallOptions (C++ function), 19	Lib3MF::CBuildItem::SetUUID (C++ function), 21
Lib3MF::CBeamLattice::GetClipping (C++ func- tion), 19	Lib3MF::CBuildItemIterator (C++ class), 22
Lib3MF::CBeamLattice::GetMinLength (C++ func- tion), 19	Lib3MF::CBuildItemIterator::Clone (C++ func- tion), 22
Lib3MF::CBeamLattice::GetRepresentation (C++ function), 19	Lib3MF::CBuildItemIterator::Count (C++ func- tion), 22
Lib3MF::CBeamLattice::SetClipping (C++ func- tion), 19	Lib3MF::CBuildItemIterator::GetCurrent (C++ function), 22
Lib3MF::CBeamLattice::SetMinLength (C++ func- tion), 19	Lib3MF::CBuildItemIterator::MoveNext (C++ function), 22
Lib3MF::CBeamLattice::SetRepresentation (C++ function), 19	Lib3MF::CBuildItemIterator::MovePrevious (C++ function), 22
Lib3MF::CBeamSet (C++ class), 20	Lib3MF::CColorGroup (C++ class), 22
Lib3MF::CBeamSet::GetBallReferenceCount (C++ function), 20	Lib3MF::CColorGroup::AddColor (C++ function), 22
Lib3MF::CBeamSet::GetBallReferences (C++ function), 20	Lib3MF::CColorGroup::GetAllPropertyIDs (C++ function), 22
Lib3MF::CBeamSet::GetIdentifier (C++ function), 20	Lib3MF::CColorGroup::GetColor (C++ function), 23
Lib3MF::CBeamSet::GetName (C++ function), 20	Lib3MF::CColorGroup::GetCount (C++ function), 22
Lib3MF::CBeamSet::GetReferenceCount (C++ function), 20	Lib3MF::CColorGroup::RemoveColor (C++ func- tion), 22
Lib3MF::CBeamSet::GetReferences (C++ function), 20	Lib3MF::CColorGroup::SetColor (C++ function), 22
Lib3MF::CBeamSet::SetBallReferences (C++ function), 20	Lib3MF::CColorGroupIterator (C++ class), 23
Lib3MF::CBeamSet::SetIdentifier (C++ function), 20	Lib3MF::CColorGroupIterator::GetCurrentColorGroup (C++ function), 23
Lib3MF::CBeamSet::SetName (C++ function), 20	Lib3MF::CComponent (C++ class), 23
Lib3MF::CBeamSet::SetReferences (C++ function), 20	Lib3MF::CComponent::GetObjectResource (C++ function), 23
Lib3MF::CBuildItem (C++ class), 21	Lib3MF::CComponent::GetObjectResourceID (C++ function), 23
Lib3MF::CBuildItem::GetMetaDataGroup (C++ function), 21	Lib3MF::CComponent::GetTransform (C++ func- tion), 23
Lib3MF::CBuildItem::GetObjectResource (C++ function), 21	Lib3MF::CComponent::GetUUID (C++ function), 23
Lib3MF::CBuildItem::GetObjectResourceID	Lib3MF::CComponent::HasTransform (C++ func- tion), 23
	Lib3MF::CComponent::SetTransform (C++ func- tion), 23
	Lib3MF::CComponent::SetUUID (C++ function), 23
	Lib3MF::CComponentsObject (C++ class), 24
	Lib3MF::CComponentsObject::AddComponent (C++ function), 24
	Lib3MF::CComponentsObject::GetComponent

(C++ function), 24	(C++ function), 16
Lib3MF::CComponentsObject::GetComponentCount (C++ function), 24	Lib3MF::CKeyStore (C++ class), 27
Lib3MF::CComponentsObjectIterator (C++ class), 24	Lib3MF::CKeyStore::AddConsumer (C++ function), 27
Lib3MF::CComponentsObjectIterator::GetCurrentComponentsObject (C++ function), 24	Lib3MF::CKeyStore::AddResourceData (C++ function), 27
Lib3MF::CCompositeMaterials (C++ class), 25	Lib3MF::CKeyStore::AddResourceDataGroup (C++ function), 27
Lib3MF::CCompositeMaterials::AddComposite (C++ function), 25	Lib3MF::CKeyStore::FindConsumer (C++ function), 27
Lib3MF::CCompositeMaterials::GetAllPropertyIDs (C++ function), 25	Lib3MF::CKeyStore::FindResourceData (C++ function), 28
Lib3MF::CCompositeMaterials::GetBaseMaterialGroup (C++ function), 25	Lib3MF::CKeyStore::FindResourceDataGroup (C++ function), 28
Lib3MF::CCompositeMaterials::GetComposite (C++ function), 25	Lib3MF::CKeyStore::GetConsumer (C++ function), 27
Lib3MF::CCompositeMaterials::GetCount (C++ function), 25	Lib3MF::CKeyStore::GetConsumerCount (C++ function), 27
Lib3MF::CCompositeMaterials::RemoveComposite (C++ function), 25	Lib3MF::CKeyStore::GetResourceData (C++ function), 28
Lib3MF::CCompositeMaterialsIterator (C++ class), 25	Lib3MF::CKeyStore::GetResourceDataCount (C++ function), 28
Lib3MF::CCompositeMaterialsIterator::GetCurrentCompositeMaterials (C++ function), 25	Lib3MF::CKeyStore::GetResourceDataGroup (C++ function), 27
Lib3MF::CConsumer (C++ class), 26	Lib3MF::CKeyStore::GetResourceDataGroupCount (C++ function), 27
Lib3MF::CConsumer::GetConsumerID (C++ function), 26	Lib3MF::CKeyStore::GetUUID (C++ function), 28
Lib3MF::CConsumer::GetKeyID (C++ function), 26	Lib3MF::CKeyStore::RemoveConsumer (C++ function), 27
Lib3MF::CConsumer::GetKeyValue (C++ function), 26	Lib3MF::CKeyStore::RemoveResourceData (C++ function), 28
Lib3MF::CContentEncryptionParams (C++ class), 26	Lib3MF::CKeyStore::RemoveResourceDataGroup (C++ function), 28
Lib3MF::CContentEncryptionParams::GetAdditionalAuthenticationData (C++ function), 26	Lib3MF::CKeyStore::SetUUID (C++ function), 29
Lib3MF::CContentEncryptionParams::GetAuthenticationTag (C++ function), 26	Lib3MF::CMeshObject (C++ class), 29
Lib3MF::CContentEncryptionParams::GetDescriptor (C++ function), 26	Lib3MF::CMeshObject::AddTriangle (C++ function), 29
Lib3MF::CContentEncryptionParams::GetEncryptionAlgorithm (C++ function), 26	Lib3MF::CMeshObject::AddVertex (C++ function), 29
Lib3MF::CContentEncryptionParams::GetInitializationVector (C++ function), 26	Lib3MF::CMeshObject::BeamLattice (C++ function), 31
Lib3MF::CContentEncryptionParams::GetKey (C++ function), 26	Lib3MF::CMeshObject::ClearAllProperties (C++ function), 30
Lib3MF::CContentEncryptionParams::GetKeyUUID (C++ function), 27	Lib3MF::CMeshObject::GetAllTriangleProperties (C++ function), 30
Lib3MF::CContentEncryptionParams::SetAuthenticationTag (C++ function), 26	Lib3MF::CMeshObject::GetObjectLevelProperty (C++ function), 30
Lib3MF::CInputVector (C++ class), 15	Lib3MF::CMeshObject::GetTriangle (C++ function), 29
Lib3MF::CInputVector::CInputVector (C++ function), 16	Lib3MF::CMeshObject::GetTriangleCount (C++ function), 29
Lib3MF::CInputVector::CInputVector::data (C++ function), 16	Lib3MF::CMeshObject::GetTriangleIndices (C++ function), 30
Lib3MF::CInputVector::CInputVector::size	Lib3MF::CMeshObject::GetTriangleProperties

(C++ function), 30  
 Lib3MF::CMeshObject::GetVertex (C++ function), 29  
 Lib3MF::CMeshObject::GetVertexCount (C++ function), 29  
 Lib3MF::CMeshObject::GetVertices (C++ function), 29  
 Lib3MF::CMeshObject::IsManifoldAndOriented (C++ function), 31  
 Lib3MF::CMeshObject::SetAllTriangleProperties (C++ function), 30  
 Lib3MF::CMeshObject::SetGeometry (C++ function), 30  
 Lib3MF::CMeshObject::SetObjectLevelProperty (C++ function), 30  
 Lib3MF::CMeshObject::SetTriangle (C++ function), 29  
 Lib3MF::CMeshObject::SetTriangleProperties (C++ function), 30  
 Lib3MF::CMeshObject::SetVertex (C++ function), 29  
 Lib3MF::CMeshObjectIterator (C++ class), 31  
 Lib3MF::CMeshObjectIterator::GetCurrentMeshObject (C++ function), 31  
 Lib3MF::CMetaData (C++ class), 31  
 Lib3MF::CMetaData::GetKey (C++ function), 31  
 Lib3MF::CMetaData::GetMustPreserve (C++ function), 32  
 Lib3MF::CMetaData::GetName (C++ function), 31  
 Lib3MF::CMetaData::GetNameSpace (C++ function), 31  
 Lib3MF::CMetaData::GetType (C++ function), 32  
 Lib3MF::CMetaData::GetValue (C++ function), 32  
 Lib3MF::CMetaData::SetMustPreserve (C++ function), 32  
 Lib3MF::CMetaData::SetName (C++ function), 31  
 Lib3MF::CMetaData::SetNameSpace (C++ function), 31  
 Lib3MF::CMetaData::SetType (C++ function), 32  
 Lib3MF::CMetaData::SetValue (C++ function), 32  
 Lib3MF::CMetaDataGroup (C++ class), 32  
 Lib3MF::CMetaDataGroup::AddMetaData (C++ function), 33  
 Lib3MF::CMetaDataGroup::GetMetaData (C++ function), 32  
 Lib3MF::CMetaDataGroup::GetMetaDataByKey (C++ function), 32  
 Lib3MF::CMetaDataGroup::GetMetaDataCount (C++ function), 32  
 Lib3MF::CMetaDataGroup::RemoveMetaData (C++ function), 33  
 Lib3MF::CMetaDataGroup::RemoveMetaDataByIndex (C++ function), 32  
 Lib3MF::CModel (C++ class), 33  
 Lib3MF::CModel::AddAttachment (C++ function), 37  
 Lib3MF::CModel::AddBaseMaterialGroup (C++ function), 36  
 Lib3MF::CModel::AddBuildItem (C++ function), 37  
 Lib3MF::CModel::AddColorGroup (C++ function), 36  
 Lib3MF::CModel::AddComponentsObject (C++ function), 36  
 Lib3MF::CModel::AddCompositeMaterials (C++ function), 37  
 Lib3MF::CModel::AddCustomContentType (C++ function), 38  
 Lib3MF::CModel::AddMeshObject (C++ function), 36  
 Lib3MF::CModel::AddMultiPropertyGroup (C++ function), 37  
 Lib3MF::CModel::AddSliceStack (C++ function), 36  
 Lib3MF::CModel::AddTexture2DFromAttachment (C++ function), 36  
 Lib3MF::CModel::AddTexture2DGroup (C++ function), 36  
 Lib3MF::CModel::CreatePackageThumbnailAttachment (C++ function), 38  
 Lib3MF::CModel::FindAttachment (C++ function), 37  
 Lib3MF::CModel::FindOrCreatePackagePart (C++ function), 33  
 Lib3MF::CModel::GetAttachment (C++ function), 37  
 Lib3MF::CModel::GetAttachmentCount (C++ function), 37  
 Lib3MF::CModel::GetBaseMaterialGroupByID (C++ function), 34  
 Lib3MF::CModel::GetBaseMaterialGroups (C++ function), 35  
 Lib3MF::CModel::GetBuildItems (C++ function), 35  
 Lib3MF::CModel::GetBuildUUID (C++ function), 35  
 Lib3MF::CModel::GetColorGroupByID (C++ function), 35  
 Lib3MF::CModel::GetColorGroups (C++ function), 35  
 Lib3MF::CModel::GetComponentsObjectByID (C++ function), 34  
 Lib3MF::CModel::GetComponentsObjects (C++ function), 35  
 Lib3MF::CModel::GetCompositeMaterials (C++ function), 36  
 Lib3MF::CModel::GetCompositeMaterialsByID (C++ function), 34  
 Lib3MF::CModel::GetKeyStore (C++ function), 38  
 Lib3MF::CModel::GetLanguage (C++ function), 33  
 Lib3MF::CModel::GetMeshObjectByID (C++ function), 34  
 Lib3MF::CModel::GetMeshObjects (C++ function), 35  
 Lib3MF::CModel::GetMetaDataGroup (C++ function), 37



---

```

Lib3MF::CModel::GetMultiPropertyGroupByID
    (C++ function), 34
Lib3MF::CModel::GetMultiPropertyGroups (C++
    function), 36
Lib3MF::CModel::GetObjects (C++ function), 35
Lib3MF::CModel::GetOutbox (C++ function), 35
Lib3MF::CModel::GetPackageThumbnailAttachment
    (C++ function), 38
Lib3MF::CModel::GetPropertyTypeByID (C++
    function), 34
Lib3MF::CModel::GetResources (C++ function), 35
Lib3MF::CModel::GetSliceStackByID (C++ func-
    tion), 35
Lib3MF::CModel::GetSliceStacks (C++ function),
    36
Lib3MF::CModel::GetTexture2DByID (C++ func-
    tion), 34
Lib3MF::CModel::GetTexture2DGroupByID (C++
    function), 34
Lib3MF::CModel::GetTexture2DGroups (C++ func-
    tion), 36
Lib3MF::CModel::GetTexture2Ds (C++ function), 35
Lib3MF::CModel::GetUnit (C++ function), 33
Lib3MF::CModel::HasPackageThumbnailAttachment
    (C++ function), 38
Lib3MF::CModel::MergeToModel (C++ function), 36
Lib3MF::CModel::QueryReader (C++ function), 34
Lib3MF::CModel::QueryWriter (C++ function), 34
Lib3MF::CModel::RemoveAttachment (C++ func-
    tion), 37
Lib3MF::CModel::RemoveBuildItem (C++ function),
    37
Lib3MF::CModel::RemoveCustomContentType
    (C++ function), 38
Lib3MF::CModel::RemovePackageThumbnailAttachment
    (C++ function), 38
Lib3MF::CModel::RootModelPart (C++ function), 33
Lib3MF::CModel::SetBuildUUID (C++ function), 35
Lib3MF::CModel::SetLanguage (C++ function), 33
Lib3MF::CModel::SetRandomNumberCallback
    (C++ function), 38
Lib3MF::CModel::SetUnit (C++ function), 33
Lib3MF::CMultiPropertyGroup (C++ class), 39
Lib3MF::CMultiPropertyGroup::AddLayer (C++
    function), 39
Lib3MF::CMultiPropertyGroup::AddMultiProperty
    (C++ function), 39
Lib3MF::CMultiPropertyGroup::GetAllPropertyIDs
    (C++ function), 39
Lib3MF::CMultiPropertyGroup::GetCount (C++
    function), 39
Lib3MF::CMultiPropertyGroup::GetLayer (C++
    function), 39
Lib3MF::CMultiPropertyGroup::GetLayerCount
    (C++ function), 39
Lib3MF::CMultiPropertyGroup::GetMultiProperty
    (C++ function), 39
Lib3MF::CMultiPropertyGroup::RemoveLayer
    (C++ function), 40
Lib3MF::CMultiPropertyGroup::RemoveMultiProperty
    (C++ function), 39
Lib3MF::CMultiPropertyGroup::SetMultiProperty
    (C++ function), 39
Lib3MF::CMultiPropertyGroupIterator (C++
    class), 40
Lib3MF::CMultiPropertyGroupIterator::GetCurrentMultiProper-
    ty (C++ function), 40
Lib3MF::CObject (C++ class), 40
Lib3MF::CObject::AssignSliceStack (C++ func-
    tion), 42
Lib3MF::CObject::ClearSliceStack (C++ func-
    tion), 41
Lib3MF::CObject::ClearThumbnailAttachment
    (C++ function), 41
Lib3MF::CObject::GetMetaDataGroup (C++ func-
    tion), 41
Lib3MF::CObject::GetName (C++ function), 40
Lib3MF::CObject::GetOutbox (C++ function), 41
Lib3MF::CObject::GetPartNumber (C++ function),
    40
Lib3MF::CObject::GetSlicesMeshResolution
    (C++ function), 41
Lib3MF::CObject::GetSliceStack (C++ function),
    41
Lib3MF::CObject::GetThumbnailAttachment
    (C++ function), 41
Lib3MF::CObject::GetType (C++ function), 40
Lib3MF::CObject::GetUUID (C++ function), 41
Lib3MF::CObject::HasSlices (C++ function), 41
Lib3MF::CObject::IsComponentsObject (C++
    function), 40
Lib3MF::CObject::IsMeshObject (C++ function), 40
Lib3MF::CObject::IsValid (C++ function), 41
Lib3MF::CObject::SetAttachmentAsThumbnail
    (C++ function), 41
Lib3MF::CObject::SetName (C++ function), 40
Lib3MF::CObject::SetPartNumber (C++ function),
    40
Lib3MF::CObject::SetSlicesMeshResolution
    (C++ function), 41
Lib3MF::CObject::SetType (C++ function), 40
Lib3MF::CObject::SetUUID (C++ function), 41
Lib3MF::CObjectIterator (C++ class), 42
Lib3MF::CObjectIterator::GetCurrentObject
    (C++ function), 42
Lib3MF::CPackagePart (C++ class), 42
Lib3MF::CPackagePart::GetPath (C++ function), 42
Lib3MF::CPackagePart::SetPath (C++ function), 42

```



Lib3MF::CReader (C++ class), 42  
 Lib3MF::CReader::AddKeyWrappingCallback (C++ function), 43  
 Lib3MF::CReader::AddRelationToRead (C++ function), 43  
 Lib3MF::CReader::GetStrictModeActive (C++ function), 43  
 Lib3MF::CReader::GetWarning (C++ function), 43  
 Lib3MF::CReader::GetWarningCount (C++ function), 43  
 Lib3MF::CReader::ReadFromBuffer (C++ function), 42  
 Lib3MF::CReader::ReadFromCallback (C++ function), 42  
 Lib3MF::CReader::ReadFromFile (C++ function), 42  
 Lib3MF::CReader::RemoveRelationToRead (C++ function), 43  
 Lib3MF::CReader::SetContentEncryptionCallback (C++ function), 44  
 Lib3MF::CReader::SetProgressCallback (C++ function), 43  
 Lib3MF::CReader::SetStrictModeActive (C++ function), 43  
 Lib3MF::CResource (C++ class), 44  
 Lib3MF::CResource::GetModelResourceID (C++ function), 44  
 Lib3MF::CResource::GetResourceID (C++ function), 44  
 Lib3MF::CResource::GetUniqueResourceID (C++ function), 44  
 Lib3MF::CResource::PackagePart (C++ function), 44  
 Lib3MF::CResource::SetPackagePart (C++ function), 44  
 Lib3MF::CResourceData (C++ class), 44  
 Lib3MF::CResourceData::GetAdditionalAuthenticationData (C++ function), 45  
 Lib3MF::CResourceData::GetCompression (C++ function), 45  
 Lib3MF::CResourceData::GetEncryptionAlgorithm (C++ function), 44  
 Lib3MF::CResourceData::GetPath (C++ function), 44  
 Lib3MF::CResourceDataGroup (C++ class), 45  
 Lib3MF::CResourceDataGroup::AddAccessRight (C++ function), 45  
 Lib3MF::CResourceDataGroup::FindAccessRightByConsumer (C++ function), 45  
 Lib3MF::CResourceDataGroup::GetKeyUUID (C++ function), 45  
 Lib3MF::CResourceDataGroup::RemoveAccessRight (C++ function), 45  
 Lib3MF::CResourceIterator (C++ class), 46  
 Lib3MF::CResourceIterator::Clone (C++ function), 46  
 Lib3MF::CResourceIterator::Count (C++ function), 46  
 Lib3MF::CResourceIterator::GetCurrent (C++ function), 46  
 Lib3MF::CResourceIterator::MoveNext (C++ function), 46  
 Lib3MF::CResourceIterator::MovePrevious (C++ function), 46  
 Lib3MF::CSlice (C++ class), 46  
 Lib3MF::CSlice::AddPolygon (C++ function), 46  
 Lib3MF::CSlice::GetPolygonCount (C++ function), 46  
 Lib3MF::CSlice::GetPolygonIndexCount (C++ function), 47  
 Lib3MF::CSlice::GetPolygonIndices (C++ function), 47  
 Lib3MF::CSlice::GetVertexCount (C++ function), 46  
 Lib3MF::CSlice::GetVertices (C++ function), 46  
 Lib3MF::CSlice::GetZTop (C++ function), 47  
 Lib3MF::CSlice::SetPolygonIndices (C++ function), 46  
 Lib3MF::CSlice::SetVertices (C++ function), 46  
 Lib3MF::CSliceStack (C++ class), 47  
 Lib3MF::CSliceStack::AddSlice (C++ function), 47  
 Lib3MF::CSliceStack::AddSliceStackReference (C++ function), 48  
 Lib3MF::CSliceStack::CollapseSliceReferences (C++ function), 48  
 Lib3MF::CSliceStack::GetBottomZ (C++ function), 47  
 Lib3MF::CSliceStack::GetOwnPath (C++ function), 48  
 Lib3MF::CSliceStack::GetSlice (C++ function), 47  
 Lib3MF::CSliceStack::GetSliceCount (C++ function), 47  
 Lib3MF::CSliceStack::GetSliceRefCount (C++ function), 47  
 Lib3MF::CSliceStack::GetSliceStackReference (C++ function), 48  
 Lib3MF::CSliceStack::SetOwnPath (C++ function), 48  
 Lib3MF::CSliceStackIterator (C++ class), 48  
 Lib3MF::CSliceStackIterator::GetCurrentSliceStack (C++ function), 48  
 Lib3MF::CTexture2D (C++ class), 48  
 Lib3MF::CTexture2D::GetAttachment (C++ function), 48  
 Lib3MF::CTexture2D::GetContentType (C++ function), 48  
 Lib3MF::CTexture2D::GetFilter (C++ function), 49  
 Lib3MF::CTexture2D::GetTileStyleUV (C++ function), 49

Lib3MF::CTexture2D::SetAttachment (C++ function), 48  
 Lib3MF::CTexture2D::SetContentType (C++ function), 49  
 Lib3MF::CTexture2D::SetFilter (C++ function), 49  
 Lib3MF::CTexture2D::SetTitleStyleUV (C++ function), 49  
 Lib3MF::CTexture2DGroup (C++ class), 49  
 Lib3MF::CTexture2DGroup::AddTex2Coord (C++ function), 49  
 Lib3MF::CTexture2DGroup::GetAllPropertyIDs (C++ function), 49  
 Lib3MF::CTexture2DGroup::GetCount (C++ function), 49  
 Lib3MF::CTexture2DGroup::GetTex2Coord (C++ function), 49  
 Lib3MF::CTexture2DGroup::GetTexture2D (C++ function), 50  
 Lib3MF::CTexture2DGroup::RemoveTex2Coord (C++ function), 50  
 Lib3MF::CTexture2DGroupIterator (C++ class), 50  
 Lib3MF::CTexture2DGroupIterator::GetCurrentTexture2DGroup (C++ function), 50  
 Lib3MF::CTexture2DIterator (C++ class), 50  
 Lib3MF::CTexture2DIterator::GetCurrentTexture2D (C++ function), 50  
 Lib3MF::CWrapper (C++ class), 6  
 Lib3MF::CWrapper::Acquire (C++ function), 6  
 Lib3MF::CWrapper::ColorToFloatRGBA (C++ function), 8  
 Lib3MF::CWrapper::ColorToRGBA (C++ function), 7  
 Lib3MF::CWrapper::CreateModel (C++ function), 6  
 Lib3MF::CWrapper::FloatRGBAToColor (C++ function), 7  
 Lib3MF::CWrapper::GetBuildInformation (C++ function), 6  
 Lib3MF::CWrapper::GetIdentityTransform (C++ function), 8  
 Lib3MF::CWrapper::GetLastError (C++ function), 7  
 Lib3MF::CWrapper::GetLibraryVersion (C++ function), 6  
 Lib3MF::CWrapper::GetPrereleaseInformation (C++ function), 6  
 Lib3MF::CWrapper::GetScaleTransform (C++ function), 8  
 Lib3MF::CWrapper::GetSpecificationVersion (C++ function), 6  
 Lib3MF::CWrapper::GetTranslationTransform (C++ function), 8  
 Lib3MF::CWrapper::GetUniformScaleTransform (C++ function), 8  
 Lib3MF::CWrapper::Release (C++ function), 6  
 Lib3MF::CWrapper::RetrieveProgressMessage (C++ function), 7  
 Lib3MF::CWrapper::RGBAToColor (C++ function), 7  
 Lib3MF::CWrapper::SetJournal (C++ function), 7  
 Lib3MF::CWriter (C++ class), 50  
 Lib3MF::CWriter::AddKeyWrappingCallback (C++ function), 51  
 Lib3MF::CWriter::GetDecimalPrecision (C++ function), 51  
 Lib3MF::CWriter::GetStreamSize (C++ function), 50  
 Lib3MF::CWriter::GetStrictModeActive (C++ function), 51  
 Lib3MF::CWriter::GetWarning (C++ function), 51  
 Lib3MF::CWriter::GetWarningCount (C++ function), 51  
 Lib3MF::CWriter::SetContentEncryptionCallback (C++ function), 52  
 Lib3MF::CWriter::SetDecimalPrecision (C++ function), 51  
 Lib3MF::CWriter::SetProgressCallback (C++ function), 51  
 Lib3MF::CWriter::SetStrictModeActive (C++ function), 51  
 Lib3MF::CWriter::WriteToBuffer (C++ function), 50  
 Lib3MF::CWriter::WriteToCallback (C++ function), 51  
 Lib3MF::CWriter::WriteToFile (C++ function), 50  
 Lib3MF::ELib3MFException (C++ class), 15  
 Lib3MF::ELib3MFException::ELib3MFException::getErrorCode (C++ function), 15  
 Lib3MF::ELib3MFException::ELib3MFException::what (C++ function), 15  
 Lib3MF::PAccessRight (C++ type), 16  
 Lib3MF::PAttachment (C++ type), 17  
 Lib3MF::PBase (C++ type), 17  
 Lib3MF::PBaseMaterialGroup (C++ type), 18  
 Lib3MF::PBaseMaterialGroupIterator (C++ type), 18  
 Lib3MF::PBeamLattice (C++ type), 19  
 Lib3MF::PBeamSet (C++ type), 20  
 Lib3MF::PBuildItem (C++ type), 21  
 Lib3MF::PBuildItemIterator (C++ type), 22  
 Lib3MF::PColorGroup (C++ type), 23  
 Lib3MF::PColorGroupIterator (C++ type), 23  
 Lib3MF::PComponent (C++ type), 24  
 Lib3MF::PComponentsObject (C++ type), 24  
 Lib3MF::PComponentsObjectIterator (C++ type), 24  
 Lib3MF::PCompositeMaterials (C++ type), 25  
 Lib3MF::PCompositeMaterialsIterator (C++ type), 25  
 Lib3MF::PConsumer (C++ type), 26  
 Lib3MF::PContentEncryptionParams (C++ type), 27  
 Lib3MF::PKeyStore (C++ type), 29

Lib3MF::PMeshObject (C++ type), 31  
 Lib3MF::PMeshObjectIterator (C++ type), 31  
 Lib3MF::PMetaData (C++ type), 32  
 Lib3MF::PMetaDataGroup (C++ type), 33  
 Lib3MF::PModel (C++ type), 38  
 Lib3MF::PMultiPropertyGroup (C++ type), 40  
 Lib3MF::PMultiPropertyGroupIterator (C++ type), 40  
 Lib3MF::PObject (C++ type), 42  
 Lib3MF::PObjectIterator (C++ type), 42  
 Lib3MF::PPackagePart (C++ type), 42  
 Lib3MF::PReader (C++ type), 44  
 Lib3MF::PResource (C++ type), 44  
 Lib3MF::PResourceData (C++ type), 45  
 Lib3MF::PResourceDataGroup (C++ type), 45  
 Lib3MF::PResourceIterator (C++ type), 46  
 Lib3MF::PSlice (C++ type), 47  
 Lib3MF::PSliceStack (C++ type), 48  
 Lib3MF::PSliceStackIterator (C++ type), 48  
 Lib3MF::PTexture2D (C++ type), 49  
 Lib3MF::PTexture2DGroup (C++ type), 50  
 Lib3MF::PTexture2DGroupIterator (C++ type), 50  
 Lib3MF::PTexture2DIterator (C++ type), 50  
 Lib3MF::PWrapper (C++ type), 8  
 Lib3MF::PWriter (C++ type), 52  
 Lib3MF\_double (C++ type), 9  
 Lib3MF\_int16 (C++ type), 9  
 Lib3MF\_int32 (C++ type), 9  
 Lib3MF\_int64 (C++ type), 9  
 Lib3MF\_int8 (C++ type), 9  
 Lib3MF\_pvoid (C++ type), 9  
 Lib3MF\_single (C++ type), 9  
 Lib3MF\_uint16 (C++ type), 9  
 Lib3MF\_uint32 (C++ type), 9  
 Lib3MF\_uint64 (C++ type), 9  
 Lib3MF\_uint8 (C++ type), 9  
 Lib3MFResult (C++ type), 9

## P

ProgressCallback (C++ type), 13

## R

RandomNumberCallback (C++ type), 14  
 ReadCallback (C++ type), 14

## S

sBall (C++ struct), 13  
 sBall::m\_Index (C++ member), 13  
 sBall::m\_Radius (C++ member), 13  
 sBeam (C++ struct), 13  
 sBeam::m\_CapModes (C++ member), 13  
 sBeam::m\_Indices (C++ member), 13  
 sBeam::m\_Radii (C++ member), 13

sBox (C++ struct), 13  
 sBox::m\_MaxCoordinate (C++ member), 13  
 sBox::m\_MinCoordinate (C++ member), 13  
 sColor (C++ struct), 13  
 sColor::m\_Alpha (C++ member), 13  
 sColor::m\_Blue (C++ member), 13  
 sColor::m\_Green (C++ member), 13  
 sColor::m\_Red (C++ member), 13  
 sCompositeConstituent (C++ struct), 12  
 sCompositeConstituent::m\_MixingRatio (C++ member), 12  
 sCompositeConstituent::m\_PropertyID (C++ member), 12  
 SeekCallback (C++ type), 14  
 sMultiPropertyLayer (C++ struct), 12  
 sMultiPropertyLayer::m\_ResourceID (C++ member), 12  
 sMultiPropertyLayer::m\_TheBlendMethod (C++ member), 12  
 sPosition (C++ struct), 12  
 sPosition2D (C++ struct), 12  
 sPosition2D::m\_Coordinates (C++ member), 12  
 sPosition::m\_Coordinates (C++ member), 12  
 sTex2Coord (C++ struct), 12  
 sTex2Coord::m\_U (C++ member), 13  
 sTex2Coord::m\_V (C++ member), 13  
 sTransform (C++ struct), 13  
 sTransform::m\_Fields (C++ member), 13  
 sTriangle (C++ struct), 12  
 sTriangle::m\_Indices (C++ member), 12  
 sTriangleProperties (C++ struct), 12  
 sTriangleProperties::m\_PropertyIDs (C++ member), 12  
 sTriangleProperties::m\_ResourceID (C++ member), 12

## W

WriteCallback (C++ type), 13